



NOTES:  
1. ARCHITECTURAL PLAN IS DIAGRAMMATIC. SEE CIVIL ENGINEERING DRAWINGS FOR SITE WORK.

LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

|                |            |             |
|----------------|------------|-------------|
| DATE           | 01-31-2025 |             |
| DRAWN          | FL         | REVIEWED VW |
| REVISIONS      | NO.        | DATE        |
|                |            | DESC.       |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
| PROJECT # 2409 |            |             |

CONSTRUCTION DOCUMENTS


NEW SITE PLAN

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

PANAMA CITY  
FLORIDA

SHEET NO.

G1.1



N

1

G2.1 G2.1

4'2'0'4'8'

SCALE: 1/4" = 1'-0"

NEW LIFE SAFETY PLAN

NOTES

1. LIFE SAFETY PLANS ARE INTENDED TO HIGHLIGHT FIRE WALLS AND EGRESS ACCESSORIES.

2. REFER TO ELECTRICAL FOR DETAILS ON EMERGENCY LIGHTING.

3. REFER TO MECHANICAL FOR DETAILS ON FIRE DAMPERS; FIRE DAMPERS REQUIRED IN FIRE WALLS AND FIRE RATED CEILING ASSEMBLIES.

LIFE SAFETY LEGEND

FEC

FIRE EXTINGUISHER CABINET

EXIT SIGN FACE & DIRECTION

XX

EXIT CAPACITY (CLEAR INCHES)

XX'

TRAVEL DISTANCE

WALL MOUNTED EXIT LIGHT

1 HOUR SHAFT WALL- HORIZ WITH 1 HOUR WALL UL #U423 FRIE TEST WH1651 -306.1

1 HOUR FIRE RATED WALL TO ROOF DECK

2 HOUR FIRE RATED WALL TO ROOF DECK

PROJECT DATA

OCCUPANCY

Occupancy(ies) / Group Classification:

EDUCATIONAL

Occupant/ Sq. Ft.: 20 NET

Total Net Floor Area: 2,726 SF

Total Occupants: 137

Type of Construction:

TYPE VB CONSTRUCTION

Protected or Unprotected:

UNPROTECTED

Sprinklered or Non-Sprinklered:

NON-SPRINKLERED

Max. Building Height: 40

Max. Number of Stories: 1

Max. Floor Area: 9,500 SF

EXITS

Minimum Number of Exits: 2

Maximum Travel Distance: 200 FT

Maximum Dead End Corridor: 20 FT

Min. Corridor/ Aisle Width: 72 IN

Minimum Stair Width: N/A

NOTE 44" if serving 50 or more people

36" if serving less than 50 people

Egress Width, Level: (No. of persons) 137 x .2 in.= 27.4

# of Exits: 2 Average Width of Exits: 72"

FIRE PROTECTION

FIRE PROTECTION REQUIREMENTS

Interior Bearing: 0 HOUR

Columns: 0 HOUR

Floor/ Ceiling: 0 HOUR

Interior Non-bearing: 0 HOUR

Beams, Girders, Trusses: 0 HOUR

Roof/ Ceiling: 0 HOUR

| CLASSIFICATION | WATER CLOSETS MALE |          | WATER CLOSETS FEMALE |          | LAVATORIES MALE & FEMALE |          | BATHTUBS/SHOWERS | DRINKING FOUNTAINS |          | SERVICE SINK |          |
|----------------|--------------------|----------|----------------------|----------|--------------------------|----------|------------------|--------------------|----------|--------------|----------|
|                | Required           | Provided | Required             | Provided | Required                 | Provided |                  | Required           | Provided | Required     | Provided |
| Educational    | 3                  | 3        | 3                    | 3        | 2                        | 7        | N/A              | 2                  | 2        | 1            | 1        |

LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

VBA DESIGN

DATE 01-31-2025

DRAWN FL

REVIEWED VW

REVISIONS

NO. DATE DES.

PROJECT # 2409

CONSTRUCTION DOCUMENTS

NEW LIFE SAFETY PLAN


NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

PANAMA CITY  
FLORIDA

SHEET NO.

G2.1





NOTES

1. UNLESS OTHERWISE NOTED, ALL NEW ROOF AND OVERHANGS TO MATCH EXISTING SLOPE, MATERIAL, AND COLOR.

LEGEND

SLOPE

X: 12

ROOF SLOPE

NEW SHINGLE

MANUFACTURER: GAF

COLOR: PEWTER GRAY

M.E.

MATCH EXISTING

ADJACENT BUILDING

D.S.

ALUMINUM DOWNSPOUTS

2x6 P.T. WD STUDS @ 16" O.C.

BRICK-INSTALL BRICK TIES @ 16" O.C. VERTICALLY AND HORIZONTALLY

VAPOR BARRIER OVER 1/2" SHEATHING

1" AIR SPACE

R-19 BATT INSULATION

5/8" GYPSUM BOARD (MOISTURE RESISTANT @ RESTROOMS)

5/8" GYPSUM BOARD (MOISTURE RESISTANT @ WET LOCATIONS)

2x4 WD STUDS @ 16" O.C. (TYP.)

SOUND ATTENUATION BATT

W1

W1R 2-HR. FIRE RATED WALL

UL Design No. W408

5/8" GYPSUM BOARD (MOISTURE RESISTANT @ WET LOCATIONS)

2x4 WD STUDS @ 16" O.C. (TYP.)

SOUND ATTENUATION BATT

5/8" DENS SHIELD TILE BACKER

CERAMIC TILE TO 5'-0" A.F.F.

5/8" GYPSUM BOARD (MOISTURE RESISTANT @ WET LOCATIONS)

2x6 WD STUDS @ 16" O.C. (TYP.)

SOUND ATTENUATION BATT

5/8" DENS SHIELD TILE BACKER

CERAMIC TILE TO 5'-0" A.F.F.

W3

NOTE: EXTEND BACKER AND TILE TO CEILING AT RESTROOMS

W4

NOTE: EXTEND BACKER AND TILE TO CEILING AT RESTROOMS

2x6 P.T. WD STUDS @ 16" O.C.

BRICK-INSTALL BRICK TIES @ 16" O.C. VERTICALLY AND HORIZONTALLY

VAPOR BARRIER OVER 1/2" SHEATHING

1" AIR SPACE

5/8" GYPSUM BOARD (MOISTURE RESISTANT @ WET LOCATIONS)

2x6 WD STUDS @ 16" O.C. (TYP.)

SOUND ATTENUATION BATT

W5

W6

2

A1.2

A1.2

WALL TYPES

SCALE: 1" = 1'-0"

CONSTRUCTION DOCUMENTS

NEW WORK ROOF PLAN & WALL TYPES

NEW STREAM BUILDING FOR HOLY NATIVITY EPISCOPAL SCHOOL

205 HAMILTON AVENUE

PANAMA CITY

FLORIDA

SHEET NO. A1.2

LICENSE NO. AR94000

PHONE: 850 769 3357

FAX: 850 763 0410

VBA DESIGN, INC.

ARCHITECTS AND PLANNERS

2424 JENKS AVENUE, SUITE B

PANAMA CITY, FLORIDA 32405

"DESIGNING A BETTER EXPERIENCE"

Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

DATE 01-31-2025


DRAWN FL

REVIEWED VW

REVISIONS

NO. DATE DESG.

PROJECT # 2409



| LEGEND                                                                              |                                                                   |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|
|  | 5" GYP. BOARD — MOISTURE RESISTANT / GREEN BOARD IN ALL WET AREAS |
|  | VINYL SOFFIT TO MATCH EXISTING                                    |
|  | SHIPLAP CEILING TO MATCH EXISTING                                 |
| ELECTRICAL LEGEND                                                                   |                                                                   |
| REFER TO ELECTRICAL PLANS FOR LOCATION OF ITEMS INDICATED IN THIS LEGEND.           |                                                                   |
|  | LED SURFACE MOUNTED LIGHT                                         |
|  | LED ROUND LENS STRIP                                              |
|  | LED SURFACE MOUNTED LIGHT                                         |
|  | LED SURFACE MOUNTED DOWNLIGHT RING                                |
|  | LED SURFACE MOUNTED LIGHT                                         |
|  | ADJUSTABLE ART LIGHT                                              |
|  | SUPPLY OR OUTSIDE AIR DUCT                                        |
|  | RETURN OR EXHAUST AIR DUCT                                        |
|  | AIR DIFFUSER                                                      |

[illegible]

## CONSTRUCTION DOCUMENTS

## NEW REFLECTED CEILING PLAN

**NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE**


PANAMA CITY

FLORIDA

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
DESIGNING A BETTER EXPERIENCE



**LICENSE NO. AR94000**  
**PHONE: 850 769 3357**  
**FAX: 850 763 0410**



LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"




|           |      |            |  |
|-----------|------|------------|--|
| DATE      |      | 01-31-2025 |  |
| DRAWN     |      | REVIEWED   |  |
| FL        |      | VW         |  |
| REVISIONS |      |            |  |
| NO.       | DATE | DESC.      |  |
|           |      |            |  |
|           |      |            |  |
|           |      |            |  |
|           |      |            |  |
|           |      |            |  |
| PROJECT # |      | 2409       |  |

PROJECT # 2409

CONSTRUCTION DOCUMENTS  
NEW EXTERIOR ELEVATIONS  
NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

SHEET NO.  
A2.1



LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"




|           |      |            |          |
|-----------|------|------------|----------|
| DATE      |      | 01-31-2025 |          |
| DRAWN     |      | FL         | REVIEWED |
|           |      |            | VW       |
| REVISIONS |      |            |          |
| NO.       | DATE | DESC.      |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |

PROJECT # 2409

CONSTRUCTION DOCUMENTS  
NEW EXTERIOR ELEVATIONS  
NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

SHEET NO.  
**A2.2**



LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"



|           |            |
|-----------|------------|
| DATE      | 01-31-2025 |
| DRAWN     | FL         |
| REVIEWED  | VW         |
| REVISIONS |            |
| NO.       | DATE       |
|           | DESC.      |
|           |            |
|           |            |
|           |            |
|           |            |

PROJECT # 2409

BUILDING SECTIONS

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE


FLORIDA

PANAMA CITY

CONSTRUCTION DOCUMENTS

SHEET NO.

A3.1



LICENSE NO. AR94000

PHONE: 850 769 3357

FAX: 850 763 0410

VBA DESIGN, INC.

ARCHITECTS AND PLANNERS

2424 JENKS AVENUE, SUITE B

PANAMA CITY, FLORIDA 32405

"DESIGNING A BETTER EXPERIENCE"

DATE: 01-31-2025

DRAWN: FL

REVIEWED: VW

REVISIONS

NO. DATE DESG.

PROJECT # 2409

CONSTRUCTION DOCUMENTS

BUILDING SECTIONS

NEW STREAM BUILDING FOR

HOLY NATIVITY EPISCOPAL SCHOOL


205 HAMILTON AVENUE

PANAMA CITY

FLORIDA

SHEET NO.

A3.2



LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"




|           |      |            |          |
|-----------|------|------------|----------|
| DATE      |      | 01-31-2025 |          |
| DRAWN     |      | FL         | REVIEWED |
|           |      |            | VW       |
| REVISIONS |      |            |          |
| NO.       | DATE | DESC.      |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |
|           |      |            |          |

PROJECT # 2409

FLORIDA

DOOR DETAILS  
NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY

CONSTRUCTION DOCUMENTS  
SHEET NO. A5.1



CONSTRUCTION DOCUMENTS

WINDOW DETAILS

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

PROJECT # 2409

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. These drawings are protected by U.S. copyright laws and violators are subject to legal recourse.

DATE 01-31-2025  
DRAWN FL REVIEWED VW  
REVISIONS  
NO. DATE DESC.  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

A

|     |                            |
|-----|----------------------------|
| PT  | PAINT                      |
| N/A | NOT APPLICABLE             |
| HM  | HOLLOW METAL               |
| AL  | ALUMINUM                   |
| WD  | SOLID WOOD                 |
| LMI | LARGE MISSILE IMPACT RATED |

|    |                         |
|----|-------------------------|
| CC | STAIN & CLEAR COAT      |
| TG | TEMPERED GLASS-1/4"     |
| WG | WIRED GLASS-1/4"        |
| FL | FIRELITE-3/8"           |
| MF | MANUFACTURER'S STANDARD |
| ME | MATCH EXISTING          |
| FG | FIBERGLASS              |

B

---

TYPE A1: MFG SINGLE CYLINDER W/ THUMB  
TURN INSIDE. INTEGRAL HEAD & FOOT BOLTS  
ON OPPOSITE LEAF

TYPE 2: BATH/BEDROOM PRIVACY LOCK  
PUSH-BUTTON LOCKING. CAN BE OPENED  
FROM OUTSIDE WITH SMALL SCREWDRIVER.  
TURNING INSIDE KNOB RELEASES  
PUSH-BUTTON.

TYPE 4: CODE LOCK  
OUTSIDE LEVEL UNLOCKED  
BY KEYPAD. INSIDE ALWAYS  
UNLOCKED

TYPE 1: PASSAGE LATCH  
BOTH LEVERS ALWAYS UNLOCKED.

TYPE 3: CLASSROOM LOCK  
OUTSIDE LOCKED & UNLOCKED BY KEY. INSIDE  
ALWAYS UNLOCKED.

## C

1. ALL HARDWARE TO MEET ADA & STATE ACCESSIBILITY STANDARDS.
2. ALL SIGNAGE SHALL COMPLY W/ STATE ADA STANDARDS.
3. ALL INTERIOR HARDWARE TBD  
EX. SCHLAGE AL SERIES NEPTUNE w/ 626 FINISH.  
CODE LOCKS TO BE KC 5000 SERIES.

4. PROVIDE WALL STOPS FOR ALL INTERIOR DOORS.
5. VENDOR TO SUBMIT HARDWARE LIST PER DOOR TO INCLUDE HINGES, CLOSERS, LEVER SETS, KICKPLATES, THRESHOLDS, WEATHER STRIPPING, AND DOOR BOTTOMS.
6. PULL DOWN ATTIC ACCESS WITH LADDER—COORDINATE WITH STRUCTURAL & MECHANICAL FOR REQUIRED CLEARANCES.

7. WHEN IN 2-HOUR FIRE RATED WALL, DOOR TO MEET OR EXCEED THE FIRE-RESISTANCE RATING REQUIRED FOR THE WALL, MINIMUM 90 MINUTES. REFERENCE 2023 FBC 716.5.
8. ALL NEW DOORS ARE TO MATCH DOORS OF EXISTING ADJACENT BUILDING.
9. INCLUDE TRANSOM WINDOW ABOVE EACH CLASSROOM DOOR AT CORRIDOR.

D

MF MANUFACTURER'S FINISH  
AL ALUMINUM  
HM HOLLOW METAL  
FX FIXED  
WD WOOD

## E

F

## F

- F


$$1/4'' = 1'-0''$$

$$1/4'' = 1'-0''$$

$$1/4'' = 1'-0''$$

FLOOR:

FLOOR:  
CONC SEALED CONCRETE  
LVT LUXURY VINYL TILE IN INTERFACE NATURAL STONES  
A00106 BOTTICINO MARBLE  
WD WOOD FLOOR IN CRESCENT HARDWOOD COLLECTION  
MARIGNY PLANK ACACIA PORT(SKU CHCMPP)

|     |                                                                         |
|-----|-------------------------------------------------------------------------|
| N/A | NOT APPLICABLE                                                          |
| WD  | WOOD BASE TO MATCH EXISTING BUILDING IN SW7756<br>HIGH REFLECTIVE WHITE |
| CTB | CERAMIC TILE BASE                                                       |

PT1 EGGSHELL LATEX PAINT (2 COATS) IN SW7006 EXTRA WHITE  
PT2 EGGSHELL LATEX PAINT (2 COATS) IN SW6243 DISTANCE  
EXT EXTERIOR-SEE A2.1 & A2.2  
CT1 CERAMIC TILE IN TILEBAR DREAMSTONE DOLOMITE SNOW 12X24  
RUNNING BOARD(MINIMUM GROUT TO CEILING)

GYP 5/8" GYPSUM BOARD (PAINTED PT3) IN SW7756 HIGH REFLECTIVE WHITE  
SL SHIPLAP (PAINTED PT3) IN SW7756 HIGH REFLECTIVE WHITE  
CT1 SUSPENDED 2X2 VINYL AC CEILING TILE  
AWN ALUMINUM CANOPY

## 1

MANUF: FORMICA 464-58  
COLOR: GRAYSTONE MATTE

SOLID SURFACE COUNTERTOP:  
MANUF: ARISTECH  
COLOR: HONEY ONYX 8750

1. KINETIC PERIMETER WORKSTATION #2826K
2. MOBILE FUME HOOD STATION #1800K
3. TALL STORAGE W/GLASS DOORS #358-4822
4. GOOSENECK FAUCET #100467

[www.diversifiedspaces.com](http://www.diversifiedspaces.com)  
CONTACT: FREY GAEDE 1-800-524-9222

1. ARAKAWA HANGING SYSTEMS  
www.arakawagrip.com  
CONTACT: 1-888-272-5292

1

- 1

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
DESIGNING A BETTER EXPERIENCE

PROJECT # 2409

|  |  |
|--|--|
|  |  |
|--|--|


## SCHEDULES

**NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE**

DANIELA CITY

SHEET NO.

### A6.1



- NOTES
- SEE MECHANICAL AND ELECTRICAL PLANS FOR LOCATION OF VENTS, SWITCHES, LIGHTS, ETC.
  - OWNER TO SELECT & CONTRACTOR TO SUPPLY AND INSTALL FIXTURES AND APPLIANCES.
  - UNLESS OTHERWISE NOTED ON ELECTRICAL PLANS, OVER-CABINET OUTLETS TO BE MOUNTED HORIZONTALLY 2" ABOVE COUNTER.
  - UNLESS OTHERWISE NOTED ON ELECTRICAL PLANS, TOGGLE SWITCHES TO BE MOUNTED AT 48" A.F.F.
  - SMART BOARD TO BE VIEWSONIC IFP8650 OR SIMILAR.

LICENSE NO. AR94000  
PHONE: 850 769 3357  
FAX: 850 763 0410

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

DATE: 01-31-2025  
DRAWN: FL  
REVIEWED: VW  
REVISIONS:  
NO. DATE DESG.  
PROJECT # 2409

CONSTRUCTION DOCUMENTS  
INTERIOR ELEVATIONS  
**NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL**  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

SHEET NO.  
**A7.1**



GENERAL NOTES:

DISCLAIMER:

1. THE FOLLOWING SPECIFICATIONS ARE AN OUTLINE OF MINIMUM MATERIAL REQUIREMENTS AND THEIR APPLICATION. MANUFACTURER SPECIFICATIONS AND LOCAL CODE REQUIREMENTS, WHEN IN EXCESS OF MINIMUM SPECIFICATION, SHALL CONTROL. IT IS THE CONTRACTOR RESPONSIBILITY TO REVIEW AND SUBMIT ALL SHOP DRAWINGS AND REPORT ALL DOCUMENT DISCREPANCIES TO THE STRUCTURAL ENGINEER PRIOR TO FABRICATION OR ERECTION.
2. AT CONSTRUCTION ISSUE, THESE DRAWINGS REPRESENT STRUCTURAL COMPONENTS IN THEIR FINAL AND FINISHED STATE. CONSTRUCTION PROCEDURES, BRACING METHODS, SAFETY PRECAUTIONS OR MECHANICAL REQUIREMENTS USED TO ERECT THEM ARE THE SOLE RESPONSIBILITY OF THE GENERAL CONTRACTOR OR SUBCONTRACTOR PERFORMING THE WORK.


BUILDING DESIGN CRITERIA:

- A. CODES
- 2023 FLORIDA BUILDING CODE  
BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE (ACI 318)  
BUILDING CODE REQUIREMENTS FOR CONCRETE MASONRY STRUCTURES (ACI 531)  
ASCE 7-22
- B. DESIGN LOADS
- ROOF DEAD LOAD 18 PSF  
ROOF LIVE LOAD 20 PSF – REDUCIBLE
- C. WIND LOADS PER ASCE 7-22 & 2023 FBC  
RISK CATEGORY II  
WIND SPEED, V = 140 MPH  
EXPOSURE CATEGORY = C  
MEAN ROOF HEIGHT, h = ±21.5 FEET  
TOPOGRAPHIC FACTOR, K<sub>zt</sub> = 1.00  
α = ±5.9 FEET  
ROOF PITCH = ±7/12  
ROOF SLOPE, θ = 30.3°

COMPONENTS AND CLADDING DESIGN PRESSURES  
(ALLOWABLE STRESS DESIGN)  
REFERENCE: CHAPTER 30 OF ASCE 7-22

| ZONE | TRIB. AREA | COMPONENT PRESSURE |              |
|------|------------|--------------------|--------------|
|      |            | POSITIVE (+)       | NEGATIVE (-) |
| ROOF | 1          | 10 +25.3           | -46.4        |
|      |            | 20 +23.1           | -39.4        |
|      |            | 50 +20.3           | -30.0        |
|      |            | 100 +18.1          | -23.0        |
|      |            | 200 +15.9          | -23.0        |
|      | 2          | 10 +25.3           | -51.1        |
|      |            | 20 +23.1           | -45.7        |
|      |            | 50 +20.3           | -38.5        |
|      |            | 100 +18.1          | -33.1        |
|      |            | 200 +15.9          | -27.7        |
| WALL | 3          | 10 +25.3           | -62.8        |
|      |            | 20 +23.1           | -54.7        |
|      |            | 50 +20.3           | -43.9        |
|      |            | 100 +18.1          | -35.8        |
|      |            | 200 +15.9          | -27.7        |
|      | 4          | 10 +27.7           | -30.0        |
|      |            | 20 +26.4           | -28.8        |
|      |            | 50 +24.8           | -27.1        |
|      |            | 100 +23.5          | -25.9        |
|      |            | 200 +22.3          | -24.6        |
| 5    | 10 +27.7   | -37.0              |              |
|      | 20 +26.4   | -34.5              |              |
|      | 50 +24.8   | -31.3              |              |
|      | 100 +23.5  | -28.8              |              |
|      | 200 +22.3  | -26.3              |              |

REFERENCE FIGURES BELOW:  
DESIGN ALL WINDOWS AND DOORS AS  
IMPACT RESISTANT FOR PRESSURE ABOVE



DESIGN WIND LOAD NOTES:

|     |                                                                                                                                                                                                                                                                                      |
|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ◆   | ULTIMATE WIND SPEED, V <sub>ult</sub> , WAS DETERMINED THE ASCE HAZARD TOOL WEBSITE.                                                                                                                                                                                                 |
| *   | REFERENCE SECTION 1609.3.1 AND/ OR TABLE 1609.3.1 OF THE 2023 FLORIDA BUILDING CODE FOR CONVERSION OF V <sub>ult</sub> TO V <sub>asf</sub>                                                                                                                                           |
| **  | SHOWN IN THIS TABLE ARE NET DESIGN WIND PRESSURES, P <sub>net</sub> , DETERMINED PER SECTION 30.5.2 OF ASCE 7-22. THESE PRESSURES ARE BASED ON ASD WIND SPEED, V <sub>asf</sub> , PER FIGURE 26.5-1A AND SHALL BE APPLIED NORMAL TO EACH BUILDING SURFACE AS SHOWN IN FIGURE 30.5-1. |
| *** | MINIMUM NET DESIGN WIND PRESSURE PER ASCE 7-22 SECTION 30.2.2.                                                                                                                                                                                                                       |

LUMBER:

1. UNLESS NOTED OTHERWISE, ALL LUMBER SHALL BE #2 KD SOUTHERN YELLOW PINE OR #2 SPRUCE-PINE-FIR WITH A MAXIMUM MOISTURE CONTENT OF 19 PERCENT.
2. ALL LUMBER IN CONTACT WITH CONCRETE OR MASONRY SHALL BE PRESSURE TREATED. ALL LUMBER EXPOSED TO EXTERIOR ENVIRONMENT SHALL BE PRESSURE TREATED.
3. EXTERIOR LOAD-BEARING STUD FRAMING SHALL BE NO. 2 SYP OR SPF: Fb=1000 PSI, E=1400 KSI.
4. INTERIOR LOAD-BEARING STUD FRAMING SHALL BE NO. 2 SYP OR SPF, SIZE SHOWN ON PLANS: Fb=1000 PSI, E=1400 KSI.
5. ROOF DECK SHALL BE MINIMUM ¾" EXTERIOR GRADE PLYWOOD ATTACHED WITH 8d RING SHANK NAILS AS SHOWN ON ATTACHMENT DETAILS.
6. INSTALL SIMPSON PSC CLIPS OR USP MODEL PC SHEATHING CLIPS AT ALL UNSUPPORTED EDGES OF ROOF DECK (ONE PER SPAN).
7. UNLESS NOTED OTHERWISE, ALL EXTERIOR WALL SHEATHING TO BE ½" PLYWOOD ATTACHED DIRECTLY TO WALL FRAMING MEMBERS. BLOCK ALL PANEL EDGES AND NAIL WITH 8d COMMON NAILS @ 4"o.c. AT ALL PANEL EDGES, BLOCKING, AND TOP & BOTTOM PLATES WITH FIELD NAILING @ 6"o.c.
8. ALL PLYWOOD PANELS SHALL BE INSTALLED IN ACCORDANCE WITH APA RECOMMENDATIONS AND RELATED SPECIFICATIONS. ORIENTED STRAND BOARD "OSB" MAY BE SUBSTITUTED FOR PLYWOOD WHERE APPROVED BY THE ARCHITECT/ENGINEER AND PROVIDED THE PANEL CONFORM TO THE APPROPRIATE APA RAINS FOR THE INTENDED APPLICATION.
9. PROVIDE A MINIMUM OF 2 STUDS NAILED TOGETHER BENEATH ALL HEADERS UNLESS NOTED OTHERWISE. USE AT LEAST 2-2x10 HEADER FOR ALL OPENINGS UP TO 4'-0" WIDE IN BEARING WALLS. USE AT LEAST 3-2x10 HEADER FOR ALL OPENINGS UP TO 8'-0" WIDE IN BEARING WALLS.
10. ALL MULTIPLE PIECE WOOD BEAMS SHALL BE CONNECTED TOGETHER WITH MINIMUM TWO ROWS OF 16d NAILS @ 12"o.c. (U.N.O.).
11. AS A MINIMUM, ANCHOR AND NAIL FRAMING SHALL COMPLY WITH "TABLE R602.3.(1) – FASTENING SCHEDULE" OF THE 2023 FLORIDA BUILDING CODE.
12. ALL BOLTS, NAILS, JOIST HANGERS, CLIPS, STRAPS, ETC THAT ARE IN CONTACT WITH PRESSURE TREATED MATERIAL SHALL BE HOT-DIPPED GALVANIZED OR STAINLESS STEEL.
13. ALL CONNECTORS AND HARDWARE SHALL BE INSTALLED IN STRICT COMPLIANCE WITH THE MANUFACTURER RECOMMENDATIONS. SIZE, QUANTITY, AND LOCATION OF NAILS AND FASTENERS SHALL CONFORM TO THE MANUFACTURERS PUBLISHED LITERATURE.
14. LVL BEAM SHALL BE 2950 Fb-2.0E AS MANUFACTURED.
15. TREATED GLULAMS TO BE MINIMUM 2400 PSI Fb & 1.8E MINIMUM.
16. TREATED PSL BEAMS TO BE MINIMUM 1885 PSI Fb, 1.49E, & SERVICE LEVEL 2 TREATMENT MINIMUM.
17. ALL EXTERIOR LVL'S TO BE WRAPPED & PROTECTED FROM THE WEATHER OR USE TREATED GLULAMS OR PSL'S.
18. ROOF SHINGLES TO BE HIGH WIND CLASS "H" WITH A MINIMUM OF 6 FASTENERS EACH.

FOUNDATION:

1. NO SOILS REPORT HAS BEEN PREPARED FOR THIS PROJECT, UNLESS NOTED OTHERWISE. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING ADEQUATE SOIL SUPPORT FOR THE FOUNDATION DESIGN, AND SHALL REPORT UNEXPECTED CONDITIONS TO THE DESIGNER.
2. ALL FOOTINGS, OR PORTIONS THEREOF, BELOW GRADE MAY BE EARTH FORMED BY NEAT EXCAVATIONS.
3. FOOTINGS TO BE CENTERED ON WALLS OR COLUMN UNLESS NOTED OTHERWISE.
4. ALLOWABLE SOIL BEARING = 1500 PSF
5. COMPACT ALL SOILS BELOW SLAB AND FOOTINGS 95% STANDARD PROCTOR DENSITY.
6. ALL SOIL FILL TO BE PLACED IN 8" LIFTS AND COMPACTED TO 95% STANDARD PROCTOR DENSITY.

WOOD ROOF TRUSSES & SPECIALTY WOOD PRODUCTS:

1. WOOD TRUSSES AS INDICATED ON THE PLANS SHALL BE DESIGNED TO MEET THE SPANS AND DESIGN INDICATED ON THESE DRAWINGS. STORAGE ERECTION AND BRACING SHALL BE IN ACCORDANCE WITH THE MANUFACTURERS PUBLISHED DRAWINGS AND INSTALLATION RECOMMENDATIONS. MANUFACTURER SHALL PROVIDE ALL SPECIALTY ITEMS AS NECESSARY FOR A COMPLETE INSTALLATION OF THE TRUSSES.
2. ALL HIGH PERFORMANCE SPECIALTY MEMBERS AS INDICATED ON THE PLANS SHALL BE FROM THE TRUSS MANUFACTURER. "LVL" MEMBERS SHALL BE LAMINATED VENEER LUMBER MEMBERS; "PSL" MEMBERS SHALL BE PARALLEL STRAND LUMBER MEMBERS; "LSL" MEMBERS SHALL BE TIMBERSTRAND LAMINATED AND PRESSED MEMBERS. ALL MEMBERS SHALL BE ONE CONTINUOUS PIECE OF SIZE INDICATED ON THE DRAWINGS. ALL ADHESIVES USED TO MANUFACTURE SPECIALTY PRODUCTS SHALL BE WATERPROOF.
3. SHOP DRAWINGS SHALL BE PREPARED FOR THE TRUSS ROOF SYSTEM. SHOP DRAWINGS SHALL INCLUDE FRAMING LAYOUT, INSTALLATION DETAILS, AND RELATED REQUIREMENTS. DRAWINGS SHALL BE SUBMITTED FOR REVIEW. MATERIAL SHOULD NOT BE FABRICATED UNTIL SUBMITTED ITEMS HAVE BEEN REVIEWED AND APPROVED BY THE ARCHITECT/ENGINEER.
4. ALTERNATE PRODUCTS BY OTHER MANUFACTURERS WITH COMPARABLE DESIGN PROPERTIES MAY BE SUBMITTED FOR REVIEW BY THE ENGINEER. ALTERNATE PRODUCTS MUST BE APPROVED IN WRITING BY THE ENGINEER/ ARCHITECT PRIOR TO MAKING ANY SUBSTITUTIONS.

STEEL:

1. STRUCTURAL STEEL SHALL MEET THE LATEST AISC "SPECIFICATION FOR THE DESIGN, FABRICATION AND ERECTION OF STRUCTURAL STEEL FOR BUILDINGS".
2. ALL STRUCTURAL STEEL TO MEET ASTM A992- f'y = 50ksi. ALL TUBING TO MEET ASTM A500, GRADE B - f'y = 46ksi.
3. WELDING SHALL CONFORM TO THE STANDARDS SET FORTH IN AWS PUBLICATION "WELDING IN BUILDING CONSTRUCTION".
4. ALL SHOP CONNECTIONS TO HAVE 3/16" FILLET WELDS MINIMUM UNLESS NOTED AS BOLTED CONNECTIONS.
5. ALL FIELD WELDS TO BE WITH E70XX ELECTRODES.
6. ALL ERECTION DRAWINGS SHALL SHOW ALL FIELD WELDS REQUIRED.
7. STRUCTURAL STEEL SHALL HAVE SP3 GRADE "POWER TOOL" CLEANING IN ACCORDANCE WITH THE STRUCTURAL STEEL PAINTING COUNCIL.
8. STRUCTURAL STEEL SHALL HAVE ONE COAT OF PRIMER EXCEPT THOSE MEMBERS THAT ARE GALVANIZED.
9. THE STEEL FRAME IS "NON-SELF SUPPORTING". ADEQUATE TEMPORARY SUPPORT MUST BE PROVIDED BY THE CONTRACTOR UNTIL REQUIRED CONNECTIONS OR ELEMENTS ARE IN PLACE.
10. ANCHOR BOLTS SHALL NOT BE MODIFIED UNLESS APPROVED BY ENGINEER.

MASONRY:

1. HOLLOW CONCRETE MASONRY UNITS SHALL CONFORM TO ASTM C-90 LIGHTWEIGHT, TYPE N-1 WITH A MINIMUM COMPRESSIVE STRENGTH f'm = 1500 PSI.
2. ALL MORTAR FOR USE IN MASONRY SHALL CONFORM TO ASTM C-270, TYPE M OR S. GROUT USED IN MASONRY SHALL BE MINIMUM 2500 PSI AND CONFORM TO ASTM C-476. MINIMUM 8 SACK MIX.
3. REINFORCING BARS TO BE GRADE 60 AND MEET ASTM A-615.
4. GROUT FILL ALL CELLS BELOW GRADE.
5. LAY ALL MASONRY IN A RUNNING BOND PATTERN.
6. PROVIDE #9 TRUSS TYPE JOINT REINFORCEMENT AT 16"o.c. FOR TYPICAL HORIZONTAL REINFORCING.
7. PROVIDE #9 TRUSS TYPE JOINT REINFORCEMENT AT 8"o.c. FOR TYPICAL HORIZONTAL REINFORCING AT PARAPET WALLS.
8. PROVIDE A MINIMUM OF 1" GROUT BETWEEN MAIN REINFORCING AND MASONRY UNITS.

CONCRETE WORK:


1. CONCRETE (NORMAL WEIGHT) COMPRESSIVE STRENGTH AT 28 DAYS SHALL BE REF. SCHEDULE BELOW
- | LOCATION      | COMPRESSION STRENGTH |
|---------------|----------------------|
| FOUNDATION    | 3000 psi             |
| SLAB ON GRADE | 3500 psi             |
| ELEVATED SLAB | 4000 psi             |
| WALLS         | 4000 psi             |
2. ALL REINFORCING SHALL MEET ASTM A615, GRADE 60. ALL WELDED WIRE FABRIC (WWF) SHALL MEET ASTM A185.
3. CONCRETE COVERAGE OF REINFORCEMENT SHALL BE:
- |           |                     |
|-----------|---------------------|
| FOOTINGS  | 3" BOTTOM AND SIDES |
| WALLS     | 1½"                 |
| SLABS     | ¾"                  |
| PEDESTALS | 1½" CLEAR OF TIES   |
4. ALL CONCRETE CONSTRUCTION SHALL CONFORM TO THE CURRENT "ACI MANUAL OF CONCRETE PLACEMENT".
5. PORTLAND CEMENT SHALL CONFORM TO ASTM C 150, TYPE I OR II.
6. ALL AGGREGATE FOR NORMAL WEIGHT CONCRETE SHALL MEET ASTM C 33.
7. ALL REINFORCING SHALL BE DETAILED, FABRICATED AND PLACED PER CRSI AND ACI STANDARDS, INCLUDING CONCRETE COVER AND BAR SUPPORTS. LAP BARS AT ALL SPLICES, INCLUDING CORNER BARS AND DOWELS, IN ACCORDANCE WITH SPICE SCHEDULE OR IN LIEU THEREOF 40 BAR DIAMETERS. LAP WWF 6" OR ONE FULL MESH, WHICHEVER IS GREATER.

WIND BORNE DEBRIS PROTECTION FOR EXTERIOR WINDOWS FBC 2023:

1. WINDOWS TO BE DESIGNED FOR A DESIGN WIND PRESSURE OF ±30 PSF (ASD), REFERENCE CHART.
2. THE CONTRACTOR MUST USE IMPACT RESISTANT WINDOWS PER ASTM E-1886 & E-1996

STRUCTURAL DRAWING INDEX:

S0.0 – STRUCTURAL NOTES  
S1.0 – FOUNDATION PLAN  
S2.0 – CEILING FRAMING PLAN  
S3.0 – ROOF FRAMING PLAN  
S4.0 – SECTIONS AND DETAILS  
S4.1 – SECTIONS AND DETAILS  
S5.0 – SECTIONS AND DETAILS  
S6.0 – SECTIONS AND DETAILS  
S7.0 – SECTIONS AND DETAILS




BARTON & SHUMER  
ENGINEERING, LLC

3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

STRUCTURAL NOTES  
NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION:



FOR PERMIT

REVISIONS:

DRAWN BY: KEP

DESIGNED BY: MKS

DATE:  
19 DEC 2024

SHEET


24149

S0.0

# FOUNDATION PLAN NEW STREAM BUILDING

203 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

**LOCATION.**



REVISIONS:

RAWN BY: KEP


DESIGNED BY: MKS


|             |  |
|-------------|--|
| DATE:       |  |
| 19 DEC 2024 |  |

SHEET


1.0



24149





**CEILING FRAMING PLAN**  
SCALE: 1/4"=1'-0"  
TOP OF WALL = +12'-0" U.N.O. = TRUSS BEARING






**BARTON & SUMER  
ENGINEERING, LLC**

3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

**ROOF FRAMING PLAN  
NEW STREAM BUILDING**

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION:



REVISIONS:


DRAWN BY: KEP

DESIGNED BY: MKS

DATE:  
19 DEC 2024

SHEET


24149  
S3.0



TYPICAL ANCHOR BOLTS

DETAIL  
NOT TO SCALE


1  
S4.0



TYPICAL CMU CORNER REINF.

DETAIL  
NOT TO SCALE


2  
S4.0



EXTERIOR WALL

SECTION  
SCALE: 3/4"=1'-0"

3  
S4.0




NOTE:  
SAW CUT JOINT WITHIN 4-12  
HOURS AFTER PLACING CONCRETE

CONTROL JOINT

DETAIL  
NOT TO SCALE


6  
S4.0



EXTERIOR WALL @ HOLDDOWN

SECTION  
SCALE: 3/4"=1'-0"


4  
S4.0



EXTERIOR WALL

SECTION  
SCALE: 3/4"=1'-0"


7  
S4.0



TYP. EXTERIOR ROOF CONSTRUCTION

SECTION  
SCALE: 3/4"=1'-0"


10  
S4.0



STEEL ANGLE ELEVATION

SECTION  
SCALE: 3/4"=1'-0"

11  
S4.0



TYP. EXTERIOR STEEL LINTEL APPLICATIONS

DETAIL  
NOT TO SCALE

8  
S4.0

| STEEL ANGLE SUPPORT/ ATTACHMENT |                                                            |
|---------------------------------|------------------------------------------------------------|
| SPAN                            | SUPPORT/ ATTACHMENT                                        |
| < 9'-0"                         | BEAR LINTEL MIN. 4" ON SURROUNDING BRICK VENEER            |
| > 9'-0"                         | ATTACH LINTEL TO WOOD HEADER W/ 3/8" LAG SCREWS @ 16" o.c. |
| CONT.*                          | ATTACH ANGLE TO EACH WOOD STUD W/ 3/8" LAG SCREW           |


\* WHERE LINTELS PLACED DIRECTLY ON TOP OF ROOF CONSTRUCTION FOR SUPPORT OF BRICK ABOVE.

NOTES:

1. STEEL LINTELS SHALL HAVE A LENGTH OF BEARING NOT LESS THAN 4 INCHES.
2. ALLOWABLE SPAN SHALL NOT EXCEED 18'-3".
3. MIN. 3/8" WIDTH OF BRICK VENEER THICKNESS SHALL BEAR ON STEEL ANGLE.
4. MAX. HEIGHT OF BRICK VENEER ABOVE STEEL LINTEL SUPPORT SHALL BE 12'-8".
5. PROVIDE MIN. 18 IN OF BRICK VENEER ON EACH SIDE OF OPENING.
6. BRICK VENEER SHALL BE SEPARATED FROM SHEATHING BY MIN. 1" NOMINAL AIR SPACE, BUT NO MORE THAN 4 1/2".
7. ROOF CONSTRUCTION WITH SLOPES GREATER THAN 7:12 BUT NO MORE THAN 12:12 SHALL HAVE MIN. 3"x3"x1/4" STEEL VERTICAL STOPS WELDED TO ANGLE @ 24" o.c.
8. PROVIDE MIN. TRPL 2x6 RAFTER WHERE STEEL ANGLE IS PLACED DIRECTLY ON TOP OF ROOF CONSTRUCTION. WOOD MEMBER ABUTTING VERTICAL STUD WALL SHALL BE ANCHORED W/ MIN. 3/8" - 5" LONG LAG SCREWS TO EVERY WOOD STUD SPACING. EACH ADDITIONAL ROOF MEMBER SHALL BE ANCHORED BY USE OF (2) 10d NAILS AT EVERY WOOD STUD SPACING.

| ALLOWABLE SPANS FOR GALV. STEEL LINTELS<br>SUPPORTING BRICK VENEER PER FBC 2023 |                |
|---------------------------------------------------------------------------------|----------------|
| LINTEL SIZE                                                                     | NO STORY ABOVE |
| L3"x3"x1/4"                                                                     | 6'-0"          |
| L4"x3"x1/4" LLV                                                                 | 8'-0"          |
| L5"x3 1/2"x3/16" LLV                                                            | 10'-0"         |
| L6"x3 1/2"x3/16" LLV                                                            | 14'-0"         |


\*\* REF. PLAN FOR SPANS GREATER THAN 12'-0".



TYP. EXTERIOR HEADER CONSTRUCTION

SECTION  
SCALE: 3/4"=1'-0"

9  
S4.0




BARTON & SUMER  
ENGINEERING, LLC

3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

SECTIONS AND DETAILS  
NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION:



REVISIONS:

DRAWN BY: KEP

DESIGNED BY: MKS


DATE:

19 DEC 2024

24149


SHEET

S4.0




EXTERIOR WALL

SECTION 1  
SCALE: 3/4"=1'-0" S4.1



EXTERIOR SLAB EDGE @ ENTRY

SECTION 2  
SCALE: 3/4"=1'-0" S4.1



**BARTON & SHUMER  
ENGINEERING, LLC**


3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

## SECTIONS AND DETAILS

### NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION.



REVISIONS:

RAWN BY: KEP


DESIGNED BY: MKS

|             |  |
|-------------|--|
| DATE:       |  |
| 19 DEC 2024 |  |


SHEET

64.1


24149



ROOF FRAMING  
SECTION 1  
SCALE: 3/4"=1'-0" S5.0




ROOF FRAMING @ GABLE END  
SECTION 2  
SCALE: 3/4"=1'-0" S5.0




ROOF FRAMING @ GABLE END @ ENTRY

SECTION 3  
SCALE: 3/4"=1'-0" S5.0




ROOF FRAMING @ GABLE END

SECTION 4  
SCALE: 3/4"=1'-0" S5.0



RADIUS BRICK LINTEL

SECTION 5  
SCALE: 3/4"=1'-0" S5.0




BARTON & SUMER  
ENGINEERING, LLC

3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

SECTIONS AND DETAILS  
NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION:



REVISIONS:

DRAWN BY: KEP


DESIGNED BY: MKS

DATE:  
19 DEC 2024

SHEET

24149

S5.0




MOBILE, AL 36606  
PHONE: 251-219-4942

## SECTIONS AND DETAILS

### NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION.




|                  |
|------------------|
| DRAWN BY: KEP    |
| DESIGNED BY: MKS |

DATE:  
19 DEC 2024


24149

36.0




ROOF FRAMING @ GIRDER TRUSS

SECTION 3  
SCALE: 3/4"=1'-0" (S6.0)




## ROOF FRAMING


SECTION 4  
SCALE: 3/4"=1'-0" S6.0




TRUSSES @ RIDGE  
**SECTION**  
SCALE: 3/4"=1'-0"  
S7.0




TOP & BTM PLATE INTERSECTION DETAIL  
**DETAIL**  
NOT TO SCALE  
S7.0



TYPICAL TOP PLATE NAILING DETAIL  
**DETAIL**  
NOT TO SCALE  
S7.0




TOP PLATE INTERSECTION DETAIL  
**DETAIL**  
NOT TO SCALE  
S7.0




**DETAIL**  
NOT TO SCALE  
S7.0

| INTERIOR WALL HEADERS |          |            |
|-----------------------|----------|------------|
| SPAN                  | HEADER   | JACK STUDS |
| <4'-0"                | (2) 2x8  | 1          |
| 4'-8'                 | (2) 2x10 | 2          |

\*\*REF PLAN FOR SPANS GREATER THAN 8'-0"



TYPICAL EXTERIOR WALL DETAIL (GARAGE)  
**DETAIL**  
NOT TO SCALE  
S7.0




TYPICAL HOLD DOWN DETAIL  
**DETAIL**  
NOT TO SCALE  
S7.0

#### WOOD TRUSSES:


##### DESIGN REQUIREMENTS:

- DL = 10 PSF TOP CHORD  
LL = 16 PSF TOP CHORD  
WL = 26 PSF NET TOP CHORD UPLIFT  
DL = 8 PSF BOTTOM CHORD  
LL = 5 PSF BOTTOM CHORD
- TRUSSES ARE TO BE DESIGNED TO BEAR ONLY ON THOSE WALLS INDICATED ON THESE DRAWINGS.
  - ALL TRUSSES TO HAVE BRIDGING AS REQUIRED BY THE MANUFACTURER.
  - ALL TRUSSES SHALL BE PLACE ACCORDING TO THE MANUFACTURER.
  - TRUSSES TO HAVE HURRICANE STRAPS AT ALL BEARING POINTS.
  - SHOP DRAWINGS SHALL BE PREPARED FOR THE TRUSS ROOF SYSTEM. SHOP DRAWINGS SHALL INCLUDE FRAMING LAYOUT, INSTALLATION DETAILS, AND RELATED REQUIREMENTS. DRAWINGS SHALL BE SUBMITTED FOR REVIEW. MATERIAL SHOULD NOT BE FABRICATED UNTIL SUBMITTED ITEMS HAVE BEEN REVIEWED AND APPROVED.




#### ROOF SHEATHING ATTACHMENT REQUIREMENTS

| THREE SECOND GUST, 140 MPH (ULT) WIND SPEED       |                                    | STRUCTURAL SHEATHING ATTACHMENT WITH 8d RING SHANK NAILS |               |
|---------------------------------------------------|------------------------------------|----------------------------------------------------------|---------------|
|                                                   | RAFTER/TRUSS SPACING (INCHES o.c.) | EDGE NAILING                                             | FIELD NAILING |
| ① INTERIOR ZONE                                   | 24" o.c.                           | 4" o.c.                                                  | 4" o.c.       |
| ② PERIMETER / EDGE ZONE                           | 24" o.c.                           | 4" o.c.                                                  | 4" o.c.       |
| ③ GABLE ENDWALL RAKE OR RAKE TRUSS W/LOOKOUTBLOCK |                                    | 4" o.c.                                                  | 4" o.c.       |



TYPICAL ROOF DIAPHRAGM  
**DETAIL**  
NOT TO SCALE  
S7.0




**BARTON & SUMER  
ENGINEERING, LLC**

3213 MIDTOWN PARK SOUTH  
MOBILE, AL 36606  
PHONE: 251-219-4942

## SECTIONS AND DETAILS NEW STREAM BUILDING

205 HAMILTON AVENUE  
PANAMA CITY, FLORIDA 32401

LOCATION:



REVISIONS:

DRAWN BY: KEP

DESIGNED BY: MKS

DATE:


19 DEC 2024

24149

SHEET

S7.0





FIRE PROTECTION NOTES

THE FIRE SPRINKLER SYSTEM DESIGN AND INSTALLATION SHALL COMPLY WITH AND BE REVIEWED BY FM GLOBAL.

THE FIRE SPRINKLER CONTRACTOR SHALL PROVIDE COMPLETE FIRE PROTECTION SYSTEM LAYOUT DOCUMENTS THOROUGHLY COORDINATED WITH THE CONSTRUCTION DOCUMENTS AND THE OTHER TRADES. ALL LAYOUT WORK SHALL BE IN ACCORDANCE WITH THE FOLLOWING;

1. NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) PAMPHLET NO. 13 (CURRENT EDITION) THE "STANDARD FOR THE INSTALLATION OF SPRINKLER SYSTEMS".
2. NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) PAMPHLET NO. 14 (CURRENT EDITION) THE "STANDARD FOR THE INSTALLATION OF STANDPIPES AND HOSE SYSTEMS".
3. NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) PAMPHLET NO. 20 (CURRENT EDITION) THE "STANDARD FOR THE INSTALLATION OF CENTRIFUGAL PUMPS".
4. NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) PAMPHLET NO. 24 (CURRENT EDITION) THE "STANDARD FOR THE INSTALLATION OF PRIVATE FIRE SERVICE MAIN AND THEIR APPURTENANCES".
5. FLORIDA BUILDING CODE (CURRENT EDITION) AND THE LIFE SAFETY CODE (NFPA 101 (CURRENT EDITION)
6. WHERE ADDITIONAL OR MORE STRINGENT REQUIREMENTS ARE NOTED ON THE DRAWINGS OR SPECIFIED BY LOCAL ORDINANCES, THE MORE STRINGENT REQUIREMENTS SHALL APPLY. PARTICULAR ATTENTION SHOULD BE GIVEN TO LOCAL ORDINANCES PERTAINING TO STANDPIPE REQUIREMENTS.
7. THE FIRE SPRINKLER CONTRACTOR SHALL SUBMIT TO THE ENGINEER OF RECORD TWO SETS OF THE FIRE SPRINKLER LAYOUT DRAWINGS, PRODUCT SUBMITTAL AND HYDRAULIC CALCULATIONS FOR REVIEW. THE FIRE SPRINKLER LAYOUT DRAWINGS AND CALCULATIONS SHALL REQUIRE THE OVERSIGHT AND SEAL OF A FLORIDA REGISTERED PROFESSIONAL ENGINEER AS A CONTRACTUAL REQUIREMENT. NO INSTALLATION SHALL PROCEED WITHOUT PRIOR APPROVAL OF THE ABOVE REFERENCED.
8. THE FIRE SPRINKLER CONTRACTOR SHALL SUBMIT THE REQUIRED FIRE PROTECTION SYSTEM LAYOUT DOCUMENTS TO THE LOCAL AUTHORITY HAVING JURISDICTION FOR APPROVAL AND PERMITTING. THE FIRE PROTECTION SYSTEM LAYOUT DOCUMENTS SHALL REQUIRE THE OVERSIGHT AND SEAL OF A FLORIDA REGISTERED PROFESSIONAL ENGINEER AS A CONTRACTUAL REQUIREMENT. NO INSTALLATION SHALL PROCEED WITHOUT PRIOR APPROVAL OF THE ABOVE REFERENCED.
9. THE PRIVATE FIRE SERVICE MAIN SHALL BE INSTALLED BY A FLORIDA CERTIFIED FIRE SPRINKLER CONTRACTOR. THIS CONTRACTOR'S WORK SHALL BEGIN AT THE POINT OF CONNECTION WHERE THE UNDERGROUND IS SOLELY DEDICATED
10. THE FIRE SPRINKLER CONTRACTOR SHALL BE RESPONSIBLE FOR CONDUCTING A CURRENT FIRE FLOW TEST. THE FIRE FLOW TEST SHALL BE WITNESSED AND APPROVED BY THE LOCAL FIRE INSPECTOR.

LIGHT HAZARD DESIGN APPROACH DATA

SYSTEM(S) TYPE: WET PIPE  
REMOTE AREA: MOST HYDRAULICALLY DEMANDING 1500 SQ. FT.  
LIGHT HAZARD DENSITY: 0.10 GPM/ SQ. FT.  
HEAD SPACING: 225 SQ. FT. PER HEAD (MAX.)


ORDINARY HAZARD GROUP I DESIGN APPROACH DATA

SYSTEM(S) TYPE: WET PIPE  
REMOTE AREA: MOST HYDRAULICALLY DEMANDING 1500 SQ. FT.  
ORDINARY HAZARD DENSITY: 0.15 GPM/ SQ. FT.  
HEAD SPACING: 130 SQ. FT. PER HEAD (MAX.)

ORDINARY HAZARD GROUP II DESIGN APPROACH DATA

SYSTEM(S) TYPE: WET PIPE  
REMOTE AREA: MOST HYDRAULICALLY DEMANDING 1500 SQ. FT.  
ORDINARY HAZARD DENSITY: 0.20 GPM/ SQ. FT.  
HEAD SPACING: 130 SQ. FT. PER HEAD (MAX.)

HAZARD CLASSIFICATIONS



INSTALLATION OF FIRE SPRINKLER SYSTEMS  
AT THE LOCATION OF THE EXISTING BUILDING

JOHNSON PEADEN ENGINEERING, INC.  
850.244.6189  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF0006882  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #74127  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peaden Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peaden Engineering, Inc.

JP-E Job Number: 2409

CONSTRUCTION DOCUMENTS

FIRE PROTECTION ATTIC PLAN

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

FLORIDA

PANAMA CITY




LICENSE NO. AP94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. and its drawings are subject to U.S. Copyright laws and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

FLORIDA PROFESSIONAL ENGINEER  
No. 60209  
December 23, 2024


DATE 12-23-2024  
DRAWN JP REVIEWED JJ  
REVISIONS  
NO. DATE DESC.  
PROJECT # 2409

FP1.2










| SIZE | 1/4 BENDS |     | 1/8 BENDS |     | 1/16 BENDS |     | TEES |     | PLUGS |     |
|------|-----------|-----|-----------|-----|------------|-----|------|-----|-------|-----|
|      | A         | B   | A         | B   | A          | B   | A    | B   | C     | D   |
| 6"   | 16"       | 10" | 9"        | 10" | 6"         | 8"  | 10"  | 12" | 10"   | 21" |
| 8"   | 22"       | 13" | 12"       | 13" | 8"         | 10" | 13"  | 16" | 12"   | 29" |
| 10"  | 26"       | 17" | 14"       | 17" | 10"        | 13" | 16"  | 20" | 14"   | 36" |
| 12"  | 29"       | 21" | 16"       | 21" | 11"        | 16" | 18"  | 24" | 16"   | 41" |
| 14"  | 35"       | 24" | 19"       | 24" | 12"        | 20" | 22"  | 27" | 18"   | 48" |
| 16"  | 38"       | 27" | 21"       | 27" | 12"        | 24" | 24"  | 30" | 20"   | 54" |

THRUST BLOCK DETAILS  
N.T.S.



TAPPING SLEEVE & VALVE DETAIL  
N.T.S.



JOHNSON PEADAR  
ENGINEERING, INC.

221 Hollywood Blvd NE  
Ft Walton Beach, FL 32548  
850.244.6189V  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF000682

1399-M Jenks Ave  
Panama City, FL 32401  
850.215.4068V  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #7417  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peadar Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peadar Engineering, Inc.

JPE Job Number: 2409

CONSTRUCTION DOCUMENTS

FIRE PROTECTION NOTES AND DETAILS

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

FLORIDA

PANAMA CITY

LICENSE NO. AP94000  
PHONE: 850.769.3357  
FAX: 850.763.0410

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"


Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. reserves the right to use any portion of these drawings for any purpose without compensation to the original owner. Violators are subject to legal recourse.

DATE: 12-23-2024  
DRAWN: JP  
REVIEWED: JJ

REVISIONS  
NO. DATE DESC.

PROJECT # 2409

SHEET NO. FP2.1



| MECHANICAL LEGEND |                                    |      |                                        |
|-------------------|------------------------------------|------|----------------------------------------|
| MARK              | DESCRIPTION                        | MARK | DESCRIPTION                            |
| CFM               | CUBIC FEET PER MINUTE              |      | TURNING VANES IN DUCT                  |
| DN                | DOWN                               |      | MANUAL DAMPER                          |
| CD                | CEILING DIFFUSER (TITUS TDCA-AA)   |      | SUPPLY OR OUTSIDE AIR DUCT IN SECTION  |
| RR                | RETURN REGISTER (TITUS 350F)       |      | RETURN OR EXHAUST AIR DUCT IN SECTION  |
| TG                | TRANSFER GRILLE (TITUS 350F)       |      | DUCT SIZE (FIRST DIMENSION AS VIEWED)  |
| LSD               | LINEAR SLOT DIFFUSER (TITUS MJ-39) |      | CEILING TYPE AIR DIFFUSER              |
| LSR               | LINEAR SLOT RETURN (TITUS MLR-39)  |      | RECTANGULAR 4-WAY SHOWN                |
| EXH               | EXHAUST                            |      | CEILING EXHAUST OR RETURN AIR REGISTER |
| W/MD              | WITH MANUAL DAMPER                 |      |                                        |
|                   | RETURN OR EXHAUST AIR              |      |                                        |
|                   | SUPPLY AIR                         |      |                                        |
|                   | FLEXIBLE DUCTWORK                  |      |                                        |
|                   | ROUND                              |      |                                        |
|                   | 1/2" DOOR UNDERCUT                 |      |                                        |

JOHNSON PEADAR  
ENGINEERING, INC.

221 Hollywood Blvd NE  
Ft Walton Beach, FL 32548  
850.244.6189V  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF0006882

1399-M Jenks Ave  
Panama City, FL 32401  
850.215.4068V  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #74127  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peadar Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peadar Engineering, Inc.

JPE Job Number: 2409

CONSTRUCTION DOCUMENTS

HVAC FLOOR PLAN

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

FLORIDA

PANAMA CITY

LICENSE NO. AP94000  
PHONE: 850.769.3357  
FAX: 850.763.0410

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

NO. 60209  
FLORIDA  
PROFESSIONAL ENGINEER





December 23, 2024

DATE: 12-23-2024  
DRAWN: JJP  
REVIEWED: JJJ

REVISIONS  
NO. DATE DESC.

PROJECT # 2409

SHEET NO.  
M1.1



**GENERAL MECHANICAL NOTES**



- FURNISH ALL LABOR, EQUIPMENT, AND MATERIALS TO PROVIDE A COMPLETE MECHANICAL SYSTEM. DUE TO THE SCHEMATIC NATURE OF THESE PLANS, THE CONTRACTOR SHALL FIELD-VERIFY LOCATIONS FOR EQUIPMENT, DUCTWORK, AND ACCESSORIES. IN ADDITION, THIS WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID CONFLICTS. THE CONTRACTOR SHALL ALSO REVIEW THE STRUCTURAL DRAWINGS BEFORE FABRICATING AND INSTALLING DUCTWORK OR EQUIPMENT.
- ALL WORK SHALL BE PERFORMED BY SKILLED AND EXPERIENCED WORKMEN. WORK SHALL COMPLY WITH ALL APPLICABLE STATE AND LOCAL CODES. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR ALL REQUIRED PERMITS, LICENSES, AND INSPECTIONS.
- ALL MATERIALS SHALL BE NEW AND WITHOUT DEFECTS. SUBMIT SHOP DRAWINGS FOR ALL MATERIALS AND EQUIPMENT. ALL WORK DONE BY THIS CONTRACTOR SHALL BE WARRANTED FOR ONE YEAR FROM THE TIME THE OWNER GIVES ACCEPTANCE OR GAINS BENEFICIAL USE, WHICHEVER IS FIRST. ALL EQUIPMENT SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.
- DUCT SIZES ON DRAWINGS ARE INSIDE CLEAR DIMENSIONS. DUCT SHALL BE OF LOW-PRESSURE (1.0" w.g.) CONSTRUCTION AS CLASSIFIED BY SMACNA UNLESS OTHERWISE NOTED. ALL DUCT SHALL HAVE MINIMUM 1" INTERNAL LINER FOR THE FIRST 20 FEET FOR SOUND ATTENUATION. AFTER 20 FEET, THE CONTRACTOR SHALL USE 2" EXTERNAL WRAP (MINIMUM R-6.0). DUCTBOARD IS NOT ALLOWED.
- FLEXIBLE DUCT MAY BE INSTALLED ONLY WHERE SHOWN ON THE DRAWINGS. DUCT SHALL BE EXTERNALLY-INSULATED CORRUGATED METAL WITH A MAXIMUM LENGTH OF 8'-0". FOR TAKE-OFFS LONGER THAN 8'-0", THE REMAINDER OF THE DISTANCE SHALL BE EXTERNALLY-WRAPPED SINGLE-WALL ROUND DUCT WITH A SPIN-IN STYLE TAP AT THE MAIN DUCT.
- HANGERS FOR EQUIPMENT AND PIPING SHALL BE SECURED TO THE BUILDING STRUCTURE. NO HANGERS SHALL BE ATTACHED TO THE FLOOR OR ROOF DECK MATERIAL OR CONCRETE DECKS LESS THAN 4" THICK.
- ALL RETURN AND EXHAUST GRILLES SHALL HAVE OPPOSED-BLADE DAMPERS. ALL SUPPLY-SIDE TAKE-OFFS SHALL HAVE A BALANCING DAMPER.
- FIRE DAMPERS AND FIRE-STOPPING SHALL BE PROVIDED FOR ANY PENETRATIONS OF FIRE-RATED PARTITIONS. VERIFY LOCATIONS OF ALL FIRE-STOPPING ON THE ARCHITECTURAL DRAWINGS.
- ALL GRILLES AND REGISTERS SHALL BE EQUAL TO TITUS WITH ALUMINUM CONSTRUCTION. SUPPLY GRILLES SHALL BE EQUAL TO MODEL TDC. SUPPLY REGISTERS SHALL BE EQUAL TO MODEL 301. RETURN, EXHAUST AND TRANSFER GRILLES SHALL BE EQUAL TO MODEL 355 WITH OPPOSED-BLADE DAMPERS. GRILLE FINISH SHALL BE APPROVED BY THE OWNER AND THE ARCHITECT.
- EQUIPMENT INSTALLED UNDER THIS CONTRACT SHALL BE ABLE TO PROVIDE THE REQUIRED CAPACITIES IN THE MIDDLE OF ITS PERFORMANCE RANGE. ALL COMPRESSORS SHALL HAVE A MINIMUM 5-YEAR WARRANTY UNLESS OTHERWISE NOTED. THE EQUIPMENT SHALL HAVE ALL THE NECESSARY CONTROLS AND ACCESSORIES TO ALLOW FOR FULL OPERATION. IF EQUIPMENT HAS COMPONENTS OF A VIBRATIVE NATURE, THE CONTRACTOR SHALL PROVIDE THE NECESSARY VIBRATION CONTROLS.
- REFRIGERANT PIPING SHALL BE HARD-DRAWN TYPE K OR L COPPER WITH COPPER SOLDER FITTINGS. PIPING SHALL BE SOLDERED WITH SILVER SOLDER AND INSULATED WITH 1/2" THICK THERMAL TUBULAR JACKETING. SEAL INSULATION JOINTS WITH TAPE AND CEMENT OR PER MANUFACTURER'S INSTRUCTIONS. PRE-INSULATED AND PRE-CHARGED REFRIGERANT LINES MAY BE USED AS PROVIDED BY THE EQUIPMENT MANUFACTURER. WHERE INSULATION IS EXPOSED TO WEATHER PROTECT LINES WITH AN ALUMINUM COVER AND PAINT TO MATCH EXTERIOR FINISH.
- CONDENSATE DRAINS SHALL BE FULL-SIZE (3/4" MINIMUM) COPPER OR SCHEDULE 40 PVC. DRAINS SHALL BE INSULATED IN THE SAME MANNER AS REFRIGERANT LINES. SPILL ON GRADE ADJACENT TO OUTDOOR UNITS.
- CONTROLS SHALL BE EQUAL TO MANUFACTURER'S CONTROLS. OUTDOOR UNITS SHALL HAVE FACTORY-WIRED TIME DELAYS, PRESSURE SWITCHES, LOW-AMBIENT CONTROLS AND DEFROST CONTROLS. THERMOSTATS SHALL BE DIGITAL AND PROGRAMMABLE WITH BATTERY BACK-UP. SETPOINTS SHALL FOLLOW DESIGN CONDITIONS OR BE AS DIRECTED BY THE OWNER. MOUNT ALL THERMOSTATS AND TEMPERATURE SENSORS 60" A.F.F.
- THE HVAC SYSTEM SHALL BE TESTED AND BALANCED ACCORDING TO AABC STANDARDS. THE CONTRACTOR SHALL PROVIDE THE ARCHITECT WITH A COPY OF THE TEST AND BALANCE REPORT AND THE OWNER WITH A LETTER STATING THAT THE SYSTEM(S) HAVE BEEN BALANCED TO WITHIN 10% OF DESIGN PARAMETERS.

| VENTILATION FAN SCHEDULE                                                                                           |     |            |            |               |          |            |          |            |                    |                      |         |
|--------------------------------------------------------------------------------------------------------------------|-----|------------|------------|---------------|----------|------------|----------|------------|--------------------|----------------------|---------|
| MARK                                                                                                               | CFM | S.P. "W.G. | MIN. POWER | VOLTAGE/PHASE | MAX. RPM | MAX. SONES | FAN TYPE | DRIVE TYPE | EQUAL TO GREENHECK | CONTROL OR INTERLOCK | NOTES   |
| 1,2,3                                                                                                              | 100 | 0.25       | 17 W       | 120/1         | 870      | 0.4        | CENTRIF. | DIRECT     | SP-A110            | MOTION SENSOR        | 1, 2, 3 |
| 4                                                                                                                  | 80  | 0.25       | 17 W       | 120/1         | 870      | 0.4        | CENTRIF. | DIRECT     | SP-A90             | LIGHT SWITCH         | 1, 2, 3 |
| 1. PROVIDE BACKDRAFT DAMPER, DISCONNECT, THERMAL OVERLOAD PROTECTION, ISOLATION KIT, MOUNTED FAN SPEED CONTROLLER. |     |            |            |               |          |            |          |            |                    |                      |         |
| 2. MOTION SENSOR SHALL HAVE OVERRIDE CONTROL.                                                                      |     |            |            |               |          |            |          |            |                    |                      |         |
| 3. DISCHARGE EXHAUST DUCT THROUGH EXHAUST LOUVER IN EXTERIOR WALL.                                                 |     |            |            |               |          |            |          |            |                    |                      |         |

| DUCTLESS SPLIT SYSTEM OUTDOOR UNIT SCHEDULE                                                                                                                               |                     |                     |      |                       |                        |                        |      |      |            |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------------------|------|-----------------------|------------------------|------------------------|------|------|------------|------------|
| UNIT NO.                                                                                                                                                                  | TOTAL COOLING (MBH) | TOTAL HEATING (MBH) | SEER | INDOOR TEMP COOL/HEAT | OUTDOOR TEMP COOL/HEAT | MITSUBISHI MDL. NUMBER | MCA  | MOCP | VOLT/PHASE | REMARKS    |
| MSCU-A                                                                                                                                                                    | 22.5                |                     | 20.5 | 80°FDB/70°FDB         | 95°FDB/47°FDB          | MSY-GL24NA             | 17.1 | 20   | 208-230/1  | 1, 2, 3, 4 |
| REMARKS                                                                                                                                                                   |                     |                     |      |                       |                        |                        |      |      |            |            |
| 1. INSTALL UNIT ON MINIMUM 4" THICK CONCRETE HOUSEKEEPING PAD. SECURE UNIT TO PAD IN ACCORDANCE WITH FBC-BUILDING.                                                        |                     |                     |      |                       |                        |                        |      |      |            |            |
| 2. INDOOR UNITS CONNECTED TO THIS HEAT PUMP SHALL BE POWERED THRU HEAT PUMP VIA FACTORY CONTROL/POWER CABLING.                                                            |                     |                     |      |                       |                        |                        |      |      |            |            |
| 3. PROVIDE REFRIGERANT LINE COVER FOR LINES ROUTED OUTSIDE ON EXTERIOR WALL.                                                                                              |                     |                     |      |                       |                        |                        |      |      |            |            |
| 4. VERIFY EQUIPMENT LOAD IN ROOM WITH OWNER PRIOR TO INSTALLING MINI-SPLIT. IF MINI-SPLIT IS NOT SIZED PROPERLY FOR FINAL EQUIPMENT LOAD CONTACT ARCHITECT FOR DIRECTION. |                     |                     |      |                       |                        |                        |      |      |            |            |

| AIR HANDLER SCHEDULE                                                                                                                                    |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------|----------------------|----------------------|----------|----------------------|----------------|-----|------|------------|------------|
| UNIT NO.                                                                                                                                                | SUPPLY AIR CFM | APPROX. E.S.P."W.G. | FAN H.P. | COOLING ENT AIR TEMP | COOLING LGV AIR TEMP | O.A. CFM | OUTDOOR TEMP-COOLING | ELEC HEAT (KW) | MCA | MOCP | VOLT/PHASE | REMARKS    |
| AH-1,2,3                                                                                                                                                | 1500           | 0.50                | 3/4      | 77.1°FDB/65.6°FWB    | 55.7°FDB/54.1°FWB    | 200      | 93°FDB/79°FWB        | 5.76           | 43  | 45   | 208v/1ø    | 1, 2, 3, 5 |
| AH-4,5                                                                                                                                                  | 1100           | 0.50                | 1/2      | 77.1°FDB/65.6°FWB    | 55.7°FDB/54.1°FWB    | 150      | 93°FDB/79°FWB        | 5.76           | 40  | 40   | 208v/1ø    | 2, 3, 4, 5 |
| REMARKS                                                                                                                                                 |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
| 1. AIR HANDLER BASIS OF DESIGN IS TRANE TEM6*48. PROVIDE TXV AND 7-DAY DIGITAL PROGRAMMABLE T'STAT WITH BATTERY BACK-UP.                                |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
| 2. PROVIDE 120v MOTORIZED DAMPER AND MANUAL BALANCING DAMPER IN ALL OUTSIDE AIR DUCTS. INSTALL DAMPERS AS CLOSE TO AIR HANDLER RETURN DUCT AS POSSIBLE. |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
| 3. PROVIDE AUXILIARY DRAIN PAN WITH FLOAT SWITCH UNDERNEATH AIR HANDLER. SPILL CONDENSATE IN EXTERIOR LANDSCAPED AREAS.                                 |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
| 4. AIR HANDLER BASIS OF DESIGN IS TRANE TEM6*36. PROVIDE TXV AND 7-DAY DIGITAL PROGRAMMABLE T'STAT WITH BATTERY BACK-UP.                                |                |                     |          |                      |                      |          |                      |                |     |      |            |            |
| 5. PROVIDE BIPOLAR IONIZATION SYSTEM EQUAL TO GPS AIR IN AIR HANDLER.                                                                                   |                |                     |          |                      |                      |          |                      |                |     |      |            |            |

| DUCTLESS SPLIT-SYSTEM AIR HANDLER SCHEDULE                                                                  |             |             |                       |                     |             |                    |      |      |            |            |
|-------------------------------------------------------------------------------------------------------------|-------------|-------------|-----------------------|---------------------|-------------|--------------------|------|------|------------|------------|
|                                                                                                             | COOLING MBH | HEATING MBH | MITSUBISHI MDL NUMBER | CONNECTED COND UNIT | REFRIG TYPE | LOCATION ROOM NAME | MCA  | MOCP | VOLT-PHASE | REMARKS    |
| 1. A                                                                                                        | 22.5        | -           | MUY-GL24NA            | CU-B                | R410A       | IT ROOM            | 1.00 | 15   | 208/230-1ø | 1, 2, 3, 4 |
| REMARKS                                                                                                     |             |             |                       |                     |             |                    |      |      |            |            |
| SPEEDS SHALL BE SET TO THE SECOND HIGHEST SPEED SETTING.                                                    |             |             |                       |                     |             |                    |      |      |            |            |
| PROVIDE INTEGRAL CONDENSATE PUMP, DISCHARGE INTO MOP SINK.                                                  |             |             |                       |                     |             |                    |      |      |            |            |
| PROVIDE HAND-HELD REMOTE CONTROL WITH WALL BRACKET.                                                         |             |             |                       |                     |             |                    |      |      |            |            |
| INDOOR UNITS CONNECTED TO THIS HEAT PUMP SHALL BE POWERED THRU HEAT PUMP VIA FACTORY CONTROL/POWER CABLING. |             |             |                       |                     |             |                    |      |      |            |            |



223 Hollywood Blvd NE  
Ft. Walton Beach, FL 32548  
850.244.6189V  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF0006882  
Tennessee #7417  
Texas #F-16637

1399-M Jenks Ave  
Panama City, FL 32401  
850.215.4068V  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #7417  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peaden Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peaden Engineering, Inc.

JPE Job Number: 2409

LICENSE NO. AP94000  
PHONE: 850.769.3357  
FAX: 850.763.0410

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

VBA DESIGN

DATE: 12-23-2024  
DRAWN: JP  
REVIEWED: JJ  
REVISIONS: NO. DATE DESC.  
PROJECT # 2409

CONSTRUCTION DOCUMENTS


HVAC SCHEDULES, NOTES AND DETAILS

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

FLORIDA

PANAMA CITY

SHEET NO. M2.1



| PLUMBING LEGEND |                        |
|-----------------|------------------------|
|                 | SOIL OR WASTE LINE     |
|                 | VENT                   |
|                 | COLD WATER (CW)        |
|                 | HOT WATER (HW)         |
|                 | HOT WATER RECIRC (HWR) |
|                 | GATE VALVE             |
|                 | T & P RELIEF VALVE     |
|                 | AUTOMATIC AIR VENT     |
|                 | FLOOR CLEANOUT         |
|                 | SHOCK ABSORBER         |
|                 | VENT THRU ROOF         |

| PLUMBING FIXTURE SCHEDULE |                                                                                                                |          |      |      |
|---------------------------|----------------------------------------------------------------------------------------------------------------|----------|------|------|
| MARK                      | FIXTURE                                                                                                        | SANITARY | C.W. | H.W. |
| HWC                       | WATER CLOSET, FLOOR, TANK TYPE ADA COMPLIANT                                                                   | 3"       | 1/2" | -    |
| HL                        | LAVATORY, WALL-HUNG WITH CARRIER, ADA COMPLIANT                                                                | 1 1/4"   | 1/2" | 1/2" |
| HU                        | URINAL, WALL-HUNG WITH CARRIER, SIPHON JET                                                                     | 2"       | 3/4" | -    |
| S-1                       | SINGLE-COMPARTMENT SINK, WALL-HUNG WITH CARRIER                                                                | 1 1/2"   | 1/2" | 1/2" |
| S-2                       | LAB SINK, UNDER COUNTER                                                                                        | 1 1/2"   | 1/2" | 1/2" |
| HEWC                      | ELEC WATER COOLER, BI-LEVEL, ADA COMPLIANT                                                                     | 1-1/2"   | 1/2" | -    |
| MS                        | MOP SINK                                                                                                       | 2"       | 1/2" | 1/2" |
| CO                        | CLEANOUT WITH BRONZE PLUG                                                                                      | 4"       | -    | -    |
| FD                        | FLOOR DRAIN W/ TRAP PRIMER                                                                                     | 3"       | -    | -    |
| HBE                       | HOSE BIBB, EXTERIOR                                                                                            | -        | 3/4" | -    |
| EYE                       | EYE WASH STATION WITH SHOWER, MIXING VALVE                                                                     | -        | 3/4" | 3/4" |
| EWB                       | ELECTRIC WATER HEATER, 50 GALLON, 12 KW NON-SIMULTANEOUS OPERATION, EQUAL TO AO SMITH DEN-50; INSTALL ON STAND | -        | 3/4" | 3/4" |
| MX-1                      | LEONARD VALVE TM-26-LF, 3/4" IN & OUT, MAX 5 PSI LOSS, MINIMUM FLOW 1.0 GPM                                    |          |      |      |
| ET-1                      | EXPANSION TANK, 2.1 GALLON, 1.48 GALLON TANK ACCEPTANCE, 150 PSI MAXIMUM PRESSURE, EQUAL TO WATTS PLT-5        |          |      |      |
| CP-1                      | CIRCULATION PUMP, 6 GPM, 25' HEAD, 115V, 1/6 HP, EQUAL TO BELL & GOSSETT MODEL PL-45                           |          |      |      |

221 Hollywood Blvd NE  
Ft Walton Beach, FL 32548  
850.244.6189V  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF0006882

1399-M Jenks Ave  
Panama City, FL 32401  
850.215.4068V  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #74127  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peadar Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peadar Engineering, Inc.

JPE Job Number: 2409

CONSTRUCTION DOCUMENTS

PLUMBING FLOOR PLAN

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

PROJECT # 2409


PLUMBING FLOOR PLAN

P1.1


LICENSE NO. AP94000  
PHONE: 850.769.3357  
FAX: 850.763.0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. Violation of these drawings and specifications may result in legal action. Violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

DATE: 12-23-2024  
DRAWN: JP  
REVIEWED: JJ  
REVISIONS:  
NO. DATE DESC.  
PROJECT # 2409



1  
P2.1 P2.1  
SANITARY SEWER RISER  
SCALE: NONE



2  
P2.1 P2.1  
DOMESTIC WATER RISER  
SCALE: NONE

**JOHNSON PEADEN ENGINEERING, INC.**

221 Hollywood Blvd NE  
Ft Walton Beach, FL 32548  
850.244.6189V  
Alabama #CD-2429-E  
Arkansas #1654  
Florida #00009014  
Georgia #PEF003983  
Louisiana #EF0006882

1399-M Jenks Ave  
Panama City, FL 32401  
850.215.4068V  
Mississippi #E-0000862  
Missouri #2018035834  
South Carolina #7058  
Tennessee #74127  
Texas #F-16637

These plans, the ideas and the concepts contained herein including any digital information are the sole property of Johnson, Peaden Engineering, Inc. They are not to be reproduced, copied, modified or changed without the expressed written permission of Johnson, Peaden Engineering, Inc.


JP E Job Number: 2409

CONSTRUCTION DOCUMENTS

PLUMBING RISERS

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

PANAMA CITY FLORIDA



December 23, 2024

|           |  |            |  |
|-----------|--|------------|--|
| DATE      |  | 12-23-2024 |  |
| DRAWN     |  | REVIEWED   |  |
| JP        |  | JJ         |  |
| REVISIONS |  |            |  |
| NO.       |  | DATE       |  |
| DESC.     |  |            |  |
|           |  |            |  |
|           |  |            |  |
|           |  |            |  |
|           |  |            |  |
|           |  |            |  |

PROJECT # 2409

SHEET NO.

P2.1

LICENSE NO. AP94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect. VBA Design, Inc. and its drawings are the property of VBA Design, Inc. and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"







## Arc Flash Hazard Appropriate PPE Required

Do not operate controls or open covers without appropriate personal protection equipment.  
Failure to comply may result in injury or death!


REFER TO NFPA 70E FOR MINIMUM PPE REQUIREMENTS

### TYPICAL ARC FLASH HAZARD LABEL DETAIL

NOT TO SCALE

#### ARC FLASH LABEL DETAIL NOTES:

- PROVIDE SELF-ADHESIVE VINYL LABEL TO AFFIX TO ALL PANEL AND SWITCHBOARDS IN ACCORDANCE WITH NEC 110.16 AND NFPA 70E.
- LABELING MAY BE COMPLETED BY EQUIPMENT MANUFACTURER, VENDOR, OR CONTRACTOR. THE CONTRACTOR SHALL VERIFY ALL PANELS AND SWITCHBOARDS ARE LABELED IN THE FIELD.
- THE LABEL SHALL BE LOCATED ON THE EQUIPMENT TO BE CLEARLY VISIBLE TO QUALIFIED PERSONS BEFORE EXAMINATION, ADJUSTMENT, SERVICING, OR MAINTENANCE OF THE EQUIPMENT.



### TYPICAL ELECTRICAL EQUIPMENT IDENTIFICATION DETAIL

NOT TO SCALE

#### ELECTRICAL EQUIPMENT IDENTIFICATION DETAIL NOTES:

- MECHANICALLY AFFIX NAMEPLATE TO PANELBOARDS, CONTROL PANELS, MOTOR CONTROL CENTERS, DISCONNECTS, STARTERS OR SIMILAR DEVICES.
- LETTERS SHALL BE WHITE ON BLACK BACKGROUND; SIZE OF LETTERS INDICATED ON DETAIL.
- INFORMATION IN LABEL IS A GENERIC EXAMPLE - DESIGNATE EQUIPMENT IN A SIMILAR WAY USING RELEVANT INFORMATION (NAME OF PANEL, VOLTS, PHASE, LOCATION, AIC RATING ETC.) ACCORDING TO EACH INDIVIDUAL LOCATION OF EQUIPMENT.



MAXIMUM AVAILABLE FAULT CURRENT: \_\_\_\_\_

NOMINAL SYSTEM VOLTAGE: \_\_\_\_\_

CLEARING TIME OF OCPD(s): \_\_\_\_\_

DATE OF LABEL ON: \_\_\_\_\_


INSTALLING ELECTRICAL CONTRACTOR NAME,  
ADDRESS & PHONE NUMBER

### TYPICAL SERVICE EQUIPMENT FAULT CURRENT LABEL DETAIL

NOT TO SCALE

#### SERVICE EQUIPMENT FAULT CURRENT LABEL DETAIL NOTES:

- PROVIDE 4" HIGH X 6" WIDE VINYL LABEL WITH BLACK LETTERING PER ANSI Z535
- LABEL SHALL MEET NEC 110.24 REQUIREMENTS



### TYPICAL GROUND BUS BAR DETAIL


NOT TO SCALE

#### GROUND BAR GENERAL NOTES:

- INSTALL GROUND BUS BAR ON COMMUNICATIONS BACKBOARD IN COMMUNICATIONS ROOM AND ELECTRICAL SERVICE ENTRANCE. MOUNT BUS BAR AT 18" AFF.
- INSTALL 1#3/0 COPPER CONDUCTOR IN 1" CONDUIT TO EACH GROUND BUS BAR FROM THE MAIN GROUND BUS BAR. INSTALL A #3/0 COPPER GROUND FROM THE MAIN BUS BAR TO THE ELECTRICAL SERVICE GROUND.

#### GROUND BAR MATERIALS:

- TIN PLATED HIGH CONDUCTIVE COPPER GROUND BAR
- WALL MOUNTING BRACKET
- INSULATORS
- 3/8" CAP SCREWS
- 3/8" LOCKWASHERS



### POWER RISER DIAGRAM

NOT TO SCALE

#### POWER RISER DIAGRAM KEYNOTES:

- PROVIDE INTEGRAL SURGE SUPPRESSOR DEVICE IN PANEL WITH 40KA PER MODE/80KA PER PHASE, INDICATING LIGHTS AND ALARM SURGE COUNTER. SURGE SUPPRESSOR SHALL BE EQUAL TO EATON SPC SERIES, VERIFY VOLTAGE AND PHASES. INSTALL ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
- SERVICE GROUND BUS BAR; SEE TYPICAL GROUND BUS BAR DETAIL
- #3/0 BARE COPPER GROUND CONDUCTOR IN 1" PVC CONDUIT TO TELE/DATA BACKBOARD ON 1ST FLOOR

### ELECTRICAL LEGEND

#### CEILING OUTLETS

"A" RECESSED 2' X 4' FLUORESCENT FIXTURE MARK "A" CIRCUIT No. 2 TYPICAL

INDICATES FIXTURE WITH EMERGENCY UNIT BATTERY PACK

EXIT LIGHT

JUNCTION BOX

EXHAUST FAN

#### WALL OUTLETS

DUPLEX RECEPTACLE - 20 AMP, 125 VOLT, 2 POLE, 3 WIRE GROUNDED TYPE, NEMA 5-20R. MOUNT 18" A.F.F. UNLESS NOTED OTHERWISE; TAMPER RESISTANT

G DUPLEX RECEPTACLE - 20 AMP, 125 VOLT, GFI, 2 POLE, 3 WIRE GROUNDED TYPE, NEMA 5-20R. MOUNT 18" A.F.F. UNLESS NOTED OTHERWISE; TAMPER RESISTANT

WP DUPLEX RECEPTACLE - 20 AMP, 125 VOLT, GFI, 2 POLE, 3 WIRE GROUNDED TYPE, NEMA 5-20R. MOUNT 18" A.F.F. UNLESS NOTED OTHERWISE; PROVIDE WEATHERPROOF BOX WITH EXTRA DUTY COVER IN ACCORDANCE WITH NEC 406.9(B) FOR RECEPTACLE TAMPER RESISTANT

QUADRUPLEX RECEPTACLE - (2) 20 AMP, 125 VOLT, 2 POLE, 3 WIRE GROUNDED TYPE, NEMA 5-20R. MOUNT 18" A.F.F. UNLESS NOTED OTHERWISE; TAMPER RESISTANT

G DUPLEX RECEPTACLE - 20 AMP, 125 VOLT, GFI, 2 POLE, 3 WIRE GROUNDED TYPE, NEMA 5-20R. MOUNT 6" ABOVE COUNTER; TAMPER RESISTANT

JUNCTION BOX WITH BLANK SCREW COVER AND FLEXIBLE CONDUIT CONNECTION

WALL MOUNTED LED AREA LIGHT FIXTURE

SIDEWALL PHOTOCELL EQUAL TO TORC #2101 (120V)

WALL MOUNTED EXIT LIGHT

#### WALL SWITCHES (UNLESS OTHERWISE NOTED, MOUNT 48" A.F.F.)

S A.C. TYPE, SINGLE POLE, 20 AMP, 120/277 VOLT

S<sub>3</sub> A.C. TYPE, 3-WAY, 20 AMP, 120/277 VOLT

S<sub>R</sub> WALL MOUNTED OCCUPANCY SENSOR; DUAL TYPE (INFRARED AND ULTRASONIC) TECHNOLOGY; MOUNT 48" AFF TO C/L; EQUAL TO WATSTOPPER DW-100

S<sub>RD</sub> WALL MOUNTED OCCUPANCY SENSOR; DUAL TYPE (INFRARED AND ULTRASONIC) TECHNOLOGY; MOUNT 48" AFF TO C/L; EQUAL TO WATSTOPPER DW-311

#### MISCELLANEOUS

A.F.F. ABOVE FINISH FLOOR

WP WEATHERPROOF

U.N.O. UNLESS NOTED OTHERWISE

FLOOR BOX WITH RECEPTACLE AND TELECOMM; SELECTION OF MATERIAL & COLOR BY ARCHITECT; CARLON E976 SERIES; SUPPLY ALL ACCESSORIES AS REQUIRED FOR A FINISHED INSTALLATION. VERIFY LOCATION WITH ARCHITECT PRIOR TO ROUGH-IN

#### TELEPHONE SYSTEM

C

#### FIRE ALARM/VOICE EVACUATION SYSTEM

FIRE ALARM/VOICE EVAC SYSTEM MANUAL PULL STATION; MT 48" AFF TO C/L

FIRE ALARM SYSTEM SIGNAL HORN/STROBE; MT 80" AFF TO BOTTOM OF HORN/STROBE.

WPH WEATHERPROOF FIRE ALARM SYSTEM SIGNAL HORN; MOUNT 80" AFF TO BOTTOM

FIRE ALARM EVAC SYSTEM STROBE; MT. 80" AFF TO C/L

FIRE ALARM SYSTEM AUTOMATIC HEAT DETECTOR; 135 DEGREE/RATE OF RISE TYPE; CEILING MOUNTED

FIRE ALARM/VOICE EVAC SYSTEM AUTOMATIC SMOKE DETECTOR; CEILING MOUNTED

FIRE ALARM SYSTEM AUTOMATIC AIR DUCT SMOKE DETECTOR MOUNTED IN AIR DUCT

NORMALLY CLOSED RELAY IN H.V.A.C CONTROL CIRCUIT TO OPEN UPON ACTUATION OF BUILDING FIRE ALARM SYSTEM TO SHUT DOWN A/C UNIT. CONTACTS RATED 5 AMPS, 120 VOLTS.

FIRE ALARM SYSTEM RACEWAY INSTALLED CONCEALED; ARROW INDICATES HOMERUN TO FIRE ALARM CONTROL PANEL

FIRE ALARM SYSTEM FLOW SWITCH

FIRE ALARM SYSTEM TAMPER SWITCH

#### PANELS AND POWER

120/208 VOLT PANELBOARD

MOTOR - SIZE AND CHARACTERISTICS AS NOTED

NON-FUSIBLE DISCONNECT SWITCH; XX/YY/ZZ WHERE X INDICATES AMPERAGE, Y INDICATES # OF POLES, AND Z INDICATES NEMA RATING

#### BRANCH CIRCUITING

RUN CONCEALED UNDER FLOOR OR IN GRADE

RUN CONCEALED IN CEILING OR WALLS

HOMERUN TO PANEL. ANY CIRCUIT WITHOUT FURTHER IDENTIFICATION INDICATES 2 #12, 1 #12 GROUND - 1/2" C; 3 #12, 1 #12 GROUND - 1/2" C; 4 #12, 1 #12 GROUND - 1/2" C; ETC. AS PER NEC. LETTERS AND NUMERALS INDICATE PANEL AND CIRCUIT NUMBER.

LIQUID-TIGHT FLEXIBLE CONDUIT CONNECTION

SURFACE MOUNTED CONDUIT; RUN PARALLEL OR PERPENDICULAR TO BUILDING LINES

#### LIGHTING CONTROLS

CEILING MOUNTED OCCUPANCY SENSOR EQUAL TO WATSTOPPER LMPC-100-5; INFRARED TECHNOLOGY; SEE LIGHTING CONTROL DETAILS

POWER PACK RELAY EQUAL TO WATSTOPPER B2150; INSTALL IN ACCESSIBLE LOCATION FOR MAINTENANCE PURPOSES

ROOM CONTROLLER WITH DIMMING CONTROLS EQUAL TO WATSTOPPER LMRC-211; 1 20 AMP CONTACTS, 0-10V CONTROLS; SEE CEILING MOUNTED MOTION DETECTOR DETAIL

ROOM CONTROLLER WITH DIMMING CONTROLS EQUAL TO WATSTOPPER LMRC-212; 1 20 AMP CONTACTS, 0-10V CONTROLS; SEE CEILING MOUNTED MOTION DETECTOR DETAIL

SLM1 DLM PROGRAMMABLE WALL SWITCH (MOUNT 48" AFF TO CENTERLINE) EQUAL TO LEGRAND LMSW-101; 2 BUTTON

SLM4 DLM PROGRAMMABLE WALL SWITCH (MOUNT 48" AFF TO CENTERLINE) EQUAL TO LEGRAND LMSW-241; 4 BUTTONS 1 ROCKER SWITCH; MULTI-ZONE SCENE DIMMING CONTROL

### ELECTRICAL GENERAL NOTES

- CONTRACTOR SHALL COORDINATE ALL WORK WITH OTHER TRADES PRIOR TO INSTALLATION. REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EXACT SIZE AND LOCATION OF EQUIPMENT WHICH IS FURNISHED BY OTHERS AND CONNECTED BY ELECTRICAL.
- RECEPTACLES, SWITCHES AND COVERPLATES COLOR SHALL BE SELECTED BY THE ARCHITECT FROM STANDARD COLORS.
- LOCATION OF LIGHTING FIXTURES, DISCONNECT SWITCHES, ETC. FOR MECHANICAL EQUIPMENT/ROOM SHALL BE COORDINATED WITH FINAL MECHANICAL EQUIPMENT LOCATION TO PROVIDE NATIONAL ELECTRIC CODE REQUIRED ACCESS SPACE.
- FINAL CONNECTION TO ALL MOTORS SHALL BE WITH FLEXIBLE CONDUIT CONNECTION.
- ALL EXIT AND EMERGENCY FIXTURES SHALL BE CONNECTED TO LIGHT CIRCUIT AHEAD OF LOCAL SWITCH.
- ALL PANELBOARDS, BACKBOARDS, TERMINAL CABINETS, DISCONNECTS, ETC SHALL HAVE CUSTOM ENGRAVED MICARTA NAMEPLATE MECHANICALLY AFFIXED IDENTIFYING SYSTEM.
- GENERAL CONTRACTOR SHALL FIELD-VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING ANY WORK, AND SHALL IMMEDIATELY NOTIFY THE ARCHITECT OF ANY DISCREPANCIES. FAILURE TO DO SO INDICATES THAT THE CONTRACTOR ACCEPTS THE CONDITIONS AS THEY EXIST, AND SHALL PERFORM THE WORK REQUIRED AS SHOWN AND SPECIFIED.
- THE ELECTRICAL CONTRACTOR SHALL OBTAIN AND REVIEW THE MECHANICAL AND SPECIAL EQUIPMENT SUBMITTALS PRIOR TO SUBMITTING THE ELECTRICAL SUBMITTALS. ANY ELECTRICAL EQUIPMENT, CONDUIT, AND WIRE SIZE CHANGES RESULTING FROM THIS REVIEW SHALL ALSO BE SUBMITTED FOR APPROVAL.
- FURNISH ALL EQUIPMENT AND LABOR, PERFORM ALL LABOR WITH SUPERVISION, BEAR ALL EXPENSES, AS NECESSARY FOR THE SATISFACTORY COMPLETION OF ALL WORK READY FOR OPERATION.
- COMPLY WITH ALL LOCAL CODE, LAWS, AND ORDINANCES APPLICABLE TO ELECTRICAL WORK, THE STATE BUILDING CODE AND THE NATIONAL ELECTRIC CODE. OBTAIN ALL PERMITS REQUIRED BY LOCAL ORDINANCES.
- OBTAIN ARCHITECTS APPROVAL OF ALL LIGHT FIXTURES, SWITCHES, RECEPTACLES, PANELBOARDS, ETC. PRIOR TO PURCHASING.
- THE GENERAL CONTRACTOR SHALL NOTIFY THE ARCHITECT IMMEDIATELY OF ANY CONFLICTS/DISCREPANCIES BETWEEN DISCIPLINES BEFORE ORDERING EQUIPMENT/MATERIALS.
- DECORATIVE COVER PLATES FOR RECEPTACLE OUTLETS, SWITCHES, ETC. SHALL BE STAINLESS STEEL; REFER TO ELECTRICAL SPECIFICATIONS
- INSTALL OCCUPANCY SENSORS AND ACCESSORIES PER MANUFACTURER'S RECOMMENDATIONS. ALL CONDUCTORS (INCLUDING CONTROLS) ASSOCIATED WITH OCCUPANCY SENSORS AND POWER PACKS SHALL BE INSTALLED IN 1/2" CONDUIT MINIMUM.
- ELECTRICAL CONTRACTOR SHALL PAINT AND LABEL ALL JUNCTION BOXES TO IDENTIFY PANEL AND CIRCUIT; SEE ELECTRICAL SPECIFICATIONS.
- ALL CONDUCTORS INDICATED ON PLAN SHALL BE COPPER.
- EQUIPMENT GROUNDING CONDUCTOR SHALL BE PULLED IN ALL BRANCH CIRCUIT WIRING. CONDUIT GROUND SHALL NOT BE ACCEPTABLE.
- THE ELECTRICAL WORK SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. ALL NOT SO INSTALLED SHALL BE REMOVED AND REPLACED AT NO COST TO THE OWNER.
- ALL CONDUCTORS LESS THAN 100A. SHALL BE COPPER #12 & #10 SOLID, #8 AND LARGER STRANDED, 600 VOLT INSULATION
- EQUIVALENT ALUMINUM CONDUCTORS ARE ACCEPTABLE FOR CONDUCTORS 100 AMPS AND ABOVE.

Raymond  
Q. Yates

Digitally signed by  
Raymond Q Yates  
Date: 2025.01.09  
11:01:21 -06'00'

YATES ENGINEERING  
SOLUTIONS

7159 Blue Jack Dr.,  
Noyette, FL 32566  
TBP# Authorization No. 30242

Phone: (850)512-9579  
Email: quinn@yateseng.com  
FL PE No. 69326

LICENSE NO. AP94000

PHONE: 850 769 3357

FAX: 850 763 0410

Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect, Yates Engineering, Inc. These drawings are the property of Yates Engineering, Inc. and shall remain the property of Yates Engineering, Inc. Any unauthorized use or reproduction of these drawings without the written consent of Yates Engineering, Inc. shall be deemed a violation and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

VBA  
DESIGN



|           |  |          |  |
|-----------|--|----------|--|
| DATE      |  | 1-9-2025 |  |
| DRAWN     |  | REVIEWED |  |
| QY        |  | QY       |  |
| REVISIONS |  |          |  |
| NO.       |  | DATE     |  |
| DESC.     |  |          |  |
|           |  |          |  |
|           |  |          |  |
|           |  |          |  |
|           |  |          |  |
|           |  |          |  |
|           |  |          |  |
|           |  |          |  |

PROJECT # 2409

ELECTRICAL LEGEND, NOTES & RISER DIAGRAM  
NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

YATES ENGINEERING  
SOLUTIONS


7159 Blue Jack Dr.,  
Noyette, FL 32566  
TBP# Authorization No. 30242

Phone: (850)512-9579  
Email: quinn@yateseng.com  
FL PE No. 69326

SHEET NO.

E0.1

| MANUFACTURERS CONSIDERED EQUAL MUST SUBMIT TO ENGINEER 14 DAYS PRIOR TO BID FOR APPROVAL |                                                                       |                                      |              |                                  |                                                                                                                                                                                   |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|--------------------------------------|--------------|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LIGHTING FIXTURE SCHEDULE                                                                |                                                                       |                                      |              |                                  |                                                                                                                                                                                   |
| MARK                                                                                     | MANUFACTURER AND CATALOG No. (or approved equal)                      | LAMPS                                |              | MOUNTING                         | REMARKS                                                                                                                                                                           |
|                                                                                          |                                                                       | No.                                  | TYPE         |                                  |                                                                                                                                                                                   |
| BPC                                                                                      | CHLORIDE CLUR3-N-W                                                    | THREE                                | 2.2W DC LED  | CEILING RECESSED                 | RECESSED COMPACT EMERGENCY LIGHTING UNIT WITH BATTERY BACKUP                                                                                                                      |
| EM2                                                                                      | H.E. WILLIAMS WETDRHL-T-WHT-MV                                        | TWO                                  | 1W LED HEADS | WALL ABOVE DOOR                  | WET LOCATION DUAL HEAD REMOTE HEAD; CONNECT TO REMOTE BATTERY IN FIXTURE XR                                                                                                       |
| L14S                                                                                     | H.E. WILLIAMS PTS-14-L45-835-SA-DIM-UNV                               | 34W LED ARRAY<br>44500 LUMEN/3500K   |              | CEILING SURFACE                  | 1X4 SHALLOW SURFACE MOUNT LED                                                                                                                                                     |
| L22S                                                                                     | H.E. WILLIAMS PTS-22-L47-835-SA-DIM-UNV                               | 38W LED ARRAY<br>4700 LUMEN/3500K    |              | CEILING SURFACE                  | 2X2 SHALLOW SURFACE MOUNT LED                                                                                                                                                     |
| LD24                                                                                     | FINELITE S19-P-ID-24'-2E-H-835-OPEN-120V-SC-FC1%-FA50-C4-FE-SW        | 160W LED ARRAY<br>21,744 LUMEN/3500K |              | CEILING PENDANT<br>AT 10'-0" AFF | LOW PROFILE LED PENDANT LUMINAIRE                                                                                                                                                 |
| LD24E                                                                                    | FINELITE S19-P-ID-24'-2E-H-835-OPEN-120V-SC-FC1%-FA50-C4-FE-SW-LGD10W | 160W LED ARRAY<br>21,744 LUMEN/3500K |              | CEILING PENDANT<br>AT 10'-0" AFF | LOW PROFILE LED PENDANT LUMINAIRE, PROVIDE 10W EMERGENCY UNIT BATTERY PACK                                                                                                        |
| LS4                                                                                      | H.E. WILLIAMS 76R-4-L52-835-DIM-UNV                                   | 36W LED ARRAY<br>5200 LUMEN/3500K    |              | CEILING SURFACE                  | 4 FT LED STRIP FIXTURE WITH ROUND LENS                                                                                                                                            |
| LS4E                                                                                     | H.E. WILLIAMS 76R-4-L52-835-DIM-UNV-EM/10W                            | 36W LED ARRAY<br>5200 LUMEN/3500K    |              | CEILING SURFACE                  | 4 FT LED STRIP FIXTURE WITH ROUND LENS WITH 10W EMERGENCY UNIT BATTERY PACK                                                                                                       |
| PD14                                                                                     | FINELITE E3-PWWD-14-H-835-F96LG-120-SC-FE                             | 56W LED ARRAY<br>5796 LUMENS/3500K   |              | CEILING PENDANT<br>AT 10'-0" AFF | 14 FT LINEAR LED WALL WASH FIXTURE                                                                                                                                                |
| SF                                                                                       | FC LIGHTING FCW3050-UNV-4K-CR185-36L-(FINISH)-LD                      | 43W LED ARRAY<br>3600 LUMENS/3500K   |              | CEILING SURFACE                  | 10" ROUND LED FIXTURE WITH IP65 RATING, 120V                                                                                                                                      |
| SFE                                                                                      | FC LIGHTING FCW3050-UNV-4K-CR185-36L-(FINISH)-LD-EB/7W                | 43W LED ARRAY<br>3600 LUMENS/3500K   |              | CEILING SURFACE                  | 10" ROUND LED FIXTURE WITH IP65 RATING, 120V, EMERGENCY UNIT BATTERY PACK                                                                                                         |
| SM                                                                                       | CAMMAN P1044-18-LN-35K-CLV-MV-WM-(FINISH)-ACC-OAH18                   | 70W LED ARRAY<br>6000 LUMEN/3500K    |              | CEILING SURFACE                  | 18" LED DECORATIVE RING FIXTURE                                                                                                                                                   |
| SMW                                                                                      | CAMMAN P1044-18-LD-40K-CLV-MV-WM-(FINISH)-WET                         | 70W LED ARRAY<br>6000 LUMEN/3500K    |              | CEILING SURFACE                  | 18" LED DECORATIVE RING FIXTURE, WET LOCATION                                                                                                                                     |
| WB                                                                                       | H.E. WILLIAMS WMPH-L30-740-T3-(FINISH)-SDGL-DIM-UNV                   | 36W LED ARRAY<br>3000 LUMEN/4000K    |              | WALL @ 9'-0" AFF                 | LED WALL MOUNTED AREA LIGHT                                                                                                                                                       |
| X                                                                                        | H.E. WILLIAMS EXIT-R-EM-WHT-SDT                                       | LED                                  |              | WALL ABOVE DOOR                  | LED EXIT LIGHT WITH THERMOPLASTIC HOUSING, EMERGENCY BATTERY BACKUP, PROVIDE DIRECTIONAL ARROWS AS INDICATED, 120V, SELF TEST DIAGNOSTICS                                         |
| XR                                                                                       | H.E. WILLIAMS EXIT/REMOTE-R-WHT-D                                     | LED                                  |              | WALL ABOVE DOOR                  | LED EXIT LIGHT WITH THERMOPLASTIC HOUSING, EMERGENCY BATTERY BACKUP, PROVIDE DIRECTIONAL ARROWS AS INDICATED, 120V, SELF TEST DIAGNOSTICS, 11 WATT REMOTE BATTERY FOR FIXTURE EM2 |
| NOTE:<br>1. FINISHES OF ALL FIXTURES SHALL BE SELECTED BY ARCHITECT                      |                                                                       |                                      |              |                                  |                                                                                                                                                                                   |



SEQUENCE OF OPERATION  
1. DURING SCHOOL HOURS - LIGHTS WILL BE ON AT 50% WITHOUT OCCUPANCY SENSOR DETECTION. WHEN OCCUPANCY SENSOR DETECTS MOTION LIGHTS WILL COME ON AT 100%. THE LMSW SWITCHES WILL NOT SERVE A FUNCTION DURING SCHOOL HOURS.  
2. DURING NON-SCHOOL HOURS - LMSW SWITCHES WILL FUNCTION AS MANUAL OVER-RIDE (ON/OFF). OCCUPANCY SENSORS WILL CONTROL LIGHTS AT 100% (ON/OFF).

CORRIDOR LIGHTING CONTROL DIAGRAM  
NOT TO SCALE

| 120/240 VOLT 1Ø 3W 600 AMP MAIN BREAKER                                                    |                       |         |     |          |      |         |      |                  |     |
|--------------------------------------------------------------------------------------------|-----------------------|---------|-----|----------|------|---------|------|------------------|-----|
| CIRCUIT BREAKER PANEL SCHEDULE                                                             |                       |         |     |          |      |         |      |                  |     |
| PANEL MP                                                                                   |                       |         |     |          |      |         |      |                  |     |
| SURFACE MOUNTED                                                                            |                       |         |     |          |      |         |      |                  |     |
| CKT                                                                                        | LOAD DESCRIPTION      | BREAKER |     | LOAD KVA |      | BREAKER |      | LOAD DESCRIPTION | CKT |
|                                                                                            |                       | POLE    | AMP |          |      | AMP     | POLE |                  |     |
| 1                                                                                          | AH-1                  | 2       | 45① | 7.20     | 4.85 | 45①     | 2    | HP-1             | 2   |
| 3                                                                                          | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 4   |
| 5                                                                                          | AH-2                  | 2       | 45① | 7.20     | 4.85 | 45①     | 2    | HP-2             | 6   |
| 7                                                                                          | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 8   |
| 9                                                                                          | AH-3                  | 2       | 45① | 7.20     | 4.85 | 45①     | 2    | HP-3             | 10  |
| 11                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 12  |
| 13                                                                                         | AH-4                  | 2       | 40① | 6.78     | 3.35 | 35①     | 2    | HP-4             | 14  |
| 15                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 16  |
| 17                                                                                         | AH-5                  | 2       | 40① | 6.78     | 3.35 | 35①     | 2    | HP-5             | 18  |
| 19                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 20  |
| 21                                                                                         | ELECTRIC WATER HEATER | 2       | 70① | 12.00    | 3.28 | 20①     | 2    | MSCU-A           | 22  |
| 23                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 24  |
| 25                                                                                         | SPARE                 | 2       | 60  |          |      | 30      | 2    | SPARE            | 26  |
| 27                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                | 28  |
| 29                                                                                         | SPACE                 | 1       | --- |          |      | ---     | 1    | SPACE            | 30  |
| 31                                                                                         | SPACE                 | 1       | --- |          |      | ---     | 1    | SPACE            | 32  |
| 33                                                                                         | SPACE                 | 1       | --- |          |      | ---     | 1    | SPACE            | 34  |
| 35                                                                                         | SPACE                 | 1       | --- |          |      | ---     | 1    | SPACE            | 36  |
| 37                                                                                         | SPACE                 | 1       | --- |          |      | ---     | 1    | SPACE            | 38  |
| 39                                                                                         | PANEL L1              | 2       | 250 | 48.63    |      | ---     | 1    | SPACE            | 40  |
| 41                                                                                         | ↓                     | ↓       | ↓   | ↓        | ↓    | ---     | 1    | SPACE            | 42  |
| TOTAL CONNECTED LOAD: 120.32 KVA<br>MINIMUM INTERRUPTING CAPACITY: 22,000 AMPS SYMMETRICAL |                       |         |     |          |      |         |      |                  |     |
| ① HACR RATED BREAKER; VERIFY SIZE REQUIRED FOR EQUIPMENT FURNISHED                         |                       |         |     |          |      |         |      |                  |     |

| 120/240 VOLT 1Ø 3W 225 AMP M.L.O.                                                         |                             |         |     |          |      |         |      |                             |     |
|-------------------------------------------------------------------------------------------|-----------------------------|---------|-----|----------|------|---------|------|-----------------------------|-----|
| CIRCUIT BREAKER PANEL SCHEDULE                                                            |                             |         |     |          |      |         |      |                             |     |
| PANEL LI                                                                                  |                             |         |     |          |      |         |      |                             |     |
| SURFACE MOUNTED                                                                           |                             |         |     |          |      |         |      |                             |     |
| CKT                                                                                       | LOAD DESCRIPTION            | BREAKER |     | LOAD KVA |      | BREAKER |      | LOAD DESCRIPTION            | CKT |
|                                                                                           |                             | POLE    | AMP |          |      | AMP     | POLE |                             |     |
| 1                                                                                         | REC-SCIENCE CLASSRM 112A    | 1       | 20  | .54      | 1.08 | 20      | 1    | REC-SCIENCE CLASSRM 103A    | 2   |
| 3                                                                                         | REC-SMARTBRD CLASSRM 112A   | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SMARTBRD CLASSRM 112A   | 4   |
| 5                                                                                         | REC-SCIENCE CLASSRM 112A    | 1       | 20  | .72      | .54  | 20      | 1    | REC-SCIENCE CLASSRM 103A    | 6   |
| 7                                                                                         | REC-SCIENCE CLASSRM 112A    | 1       | 20  | .54      | .54  | 20      | 1    | REC-SCIENCE CLASSRM 105A    | 8   |
| 9                                                                                         | REC-CLASSRM 112A FUME HOOD  | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SMARTBRD CLASSRM 105A   | 10  |
| 11                                                                                        | REC-SCIENCE CLASSRM 112A    | 1       | 20  | .72      | 1.08 | 20      | 1    | REC-SCIENCE CLASSRM 105A    | 12  |
| 13                                                                                        | REC-SCIENCE CLASSRM 112A    | 1       | 20  | .54      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 103B      | 14  |
| 15                                                                                        | REC-TECH CLASSRM 109A       | 1       | 20  | 1.26     | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 103B      | 16  |
| 17                                                                                        | REC-TECH CLASSRM 109A       | 1       | 20  | .54      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 103B      | 18  |
| 19                                                                                        | REC-SMARTBRD CLASSRM 109A   | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 103B      | 20  |
| 21                                                                                        | REC-SUPPLY CARPET 112B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 103B      | 22  |
| 23                                                                                        | REC-SUPPLY CARPET 112B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 105B      | 24  |
| 25                                                                                        | REC-SUPPLY CARPET 112B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 105B      | 26  |
| 27                                                                                        | REC-SUPPLY CARPET 112B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 105B      | 28  |
| 29                                                                                        | REC-SUPPLY CARPET 112B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 105B      | 30  |
| 31                                                                                        | REC-SUPPLY CARPET 109B      | 1       | 20  | 1.0      | 1.0  | 20      | 1    | REC-SUPPLY CLOSET 105B      | 32  |
| 33                                                                                        | REC-SUPPLY CARPET 109B      | 1       | 20  | 1.0      | 1.26 | 20      | 1    | REC-PORCH,CLOSET,RESTRMS    | 34  |
| 35                                                                                        | REC-SUPPLY CARPET 109B      | 1       | 20  | 1.0      | 1.20 | 20      | 1    | REC-DRINKING FOUNTAIN       | 36  |
| 37                                                                                        | REC-SUPPLY CARPET 109B      | 1       | 20  | 1.0      | 2.50 | 30      | 1    | UPS RECEPTACLE              | 38  |
| 39                                                                                        | REC-SUPPLY CARPET 109B      | 1       | 20  | 1.0      | .72  | 20      | 1    | REC-TBB                     | 40  |
| 41                                                                                        | FIRE ALARM CONTROL PANEL    | 1       | 20① | .20      | .36  | 20      | 1    | ACCESS CONTROL PANEL        | 42  |
| 43                                                                                        | DOOR LOCK-NORTH DOOR        | 1       | 20  | .20      | 1.26 | 20      | 1    | REC-CLOSET,RESTRM,MECH,EXTR | 44  |
| 45                                                                                        | DOOR LOCK-SOUTH DOOR        | 1       | 20  | .20      | 1.0  | 20      | 1    | VENDING MACHINE             | 46  |
| 47                                                                                        | REC-CORRIDOR                | 1       | 20  | .72      | .20  | 20      | 1    | CIRCULATION PUMP            | 48  |
| 49                                                                                        | LTS-EXTERIOR                | 1       | 20  | .74      | .70  | 20      | 1    | LTS-CLASSRM 103A,RESTRM,SUP | 50  |
| 51                                                                                        | LTS-CLASSRM 105A,RESTRM,SUP | 1       | 20  | .70      | .70  | 20      | 1    | LTS-CLASSRM 112A,RESTRM,SUP | 52  |
| 53                                                                                        | LTS-CLASSRM 105A,RESTRM,SUP | 1       | 20  | .70      | .55  | 20      | 1    | LTS-CORRIDOR                | 54  |
| 55                                                                                        | REC-TECH CLASSRM 109A       | 1       | 20  | .36      | .36  | 20      | 1    | REC-TECH CLASSRM 109A       | 56  |
| 57                                                                                        | REC-TECH CLASSRM 109A       | 1       | 20  | .18      | .72  | 20      | 1    | FLOOR REC-TECH CLSSRM 109A  | 58  |
| 59                                                                                        | ↓                           | ↓       | ↓   | ↓        | ↓    | ↓       | ↓    | ↓                           | 60  |
| 61                                                                                        | SPARE                       | 1       | 20  |          |      | 20      | 1    | SPARE                       | 62  |
| 63                                                                                        | SPARE                       | 1       | 20  |          |      | 20      | 1    | SPARE                       | 64  |
| 65                                                                                        | SPARE                       | 1       | 20  |          |      | 20      | 1    | SPARE                       | 66  |
| 67                                                                                        | SPARE                       | 1       | 20  |          |      | 20      | 1    | SPARE                       | 68  |
| 69                                                                                        | SPACE                       | 1       | --- |          |      | ---     | 1    | SPACE                       | 70  |
| 71                                                                                        | SPACE                       | 1       | --- |          |      | ---     | 1    | SPACE                       | 72  |
| TOTAL CONNECTED LOAD: 48.63 KVA<br>MINIMUM INTERRUPTING CAPACITY: 22,000 AMPS SYMMETRICAL |                             |         |     |          |      |         |      |                             |     |
| ① PROVIDE HANDLE LOCK-ON BREAKER                                                          |                             |         |     |          |      |         |      |                             |     |

YATESENGINEERING  
SOLUTIONS

7159 Blue Jack Dr.  
Noyah, FL 32566  
FBPE Authorization No. 30242

Phone: (850)512-9579  
Email: quinn@yateseng.com  
FL PE No. 68326

LICENSE NO. AP94000  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect, VBA Design, Inc. These drawings are the property of VBA Design, Inc. and shall remain the property of VBA Design, Inc. for all purposes. Violators are subject to legal recourse.


VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"


RAYMOND Q. YATES  
Professional Engineer  
No. 68326  
Exp. 9-2025

DATE 1-9-2025  
DRAWN QY  
REVISIONS  
NO. DATE DESC.  
PROJECT # 2409

SCHEDULES & DETAILS  
NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE  
PANAMA CITY  
FLORIDA

CONSTRUCTION DOCUMENTS  
E0.2





## FIRE ALARM/MASS NOTIFICATION RISER DIAGRAM


NOT TO SCALE

### FIRE ALARM SYSTEM RISER DIAGRAM GENERAL NOTES:

1. FURNISH FIRE ALARM SYSTEM WITH NECESSARY NETWORK CARD, MODULES, ACCESSORIES, ETC. AS REQUIRED TO FUNCTION AS INDICATED.
2. ALL WORK SHALL BE IN ACCORDANCE WITH NFPA 72 AND ALL STATE AND LOCAL REQUIREMENTS
3. CONTRACTOR SHALL PAY FOR ANY STATE AND LOCAL FEES AND PERMITS ASSOCIATED WITH INSTALLATION OF SYSTEM.
4. FIRE ALARM SYSTEM SHALL BE INSTALLED BY A FIRE ALARM CONTRACTOR LICENSED IN THE STATE OF FLORIDA.
5. PROVIDE ADDRESSABLE TYPE FIRE ALARM/MASS NOTIFICATION CONTROL PANEL.
6. FIRE ALARM CONTRACTOR SHALL PROVIDE ALL DEVICES, INCLUDING DUCT DETECTORS

### KEYNOTES:

- ① COORDINATE FLOOR BOX LOCATION WITH ARCHITECT/OWNER PRIOR TO ROUGH-IN



FIRE ALARM SYSTEM PLAN

SCALE: 1/4"=1'-0"

YATES ENGINEERING SOLUTIONS

7159 Blue Jack Dr.  
Navy, FL 32566  
Phone: (850) 512-9579  
Email: quinn@yateseng.com  
FL PE No. 68326

CONSTRUCTION DOCUMENTS

FIRE ALARM SYSTEM PLAN

NEW STREAM BUILDING FOR  
HOLY NATIVITY EPISCOPAL SCHOOL  
205 HAMILTON AVENUE

PANAMA CITY FLORIDA

SHEET NO.

E1.2

THIS DRAWING HAS BEEN ELECTRONICALLY SIGNED AND SEALED BY R. Q. YATES, P.E.  
THE SIGNATURE AND SEAL ARE CONSIDERED VALID AND TRUE AND THE SIGN  
THESE DRAWINGS HAVE BEEN REVIEWED AND APPROVED FOR THE DESIGNING ENGINEER.



DATE 1-9-2025

| NO. | DATE     | DESC.             | QTY | REVIEWED | QTY |
|-----|----------|-------------------|-----|----------|-----|
| 1   | 1-9-2025 | ISSUED FOR PERMIT |     |          |     |
| 2   |          |                   |     |          |     |
| 3   |          |                   |     |          |     |
| 4   |          |                   |     |          |     |
| 5   |          |                   |     |          |     |
| 6   |          |                   |     |          |     |
| 7   |          |                   |     |          |     |
| 8   |          |                   |     |          |     |
| 9   |          |                   |     |          |     |
| 10  |          |                   |     |          |     |

PROJECT # 2409

LICENSE NO. AP94000


PHONE: 850 769 3357

FAX: 850 763 0410

Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect, VBA Design, Inc. These drawings are the property of VBA Design, Inc. and violators are subject to legal recourse.

VBA DESIGN, INC.  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"






**SEQUENCE OF OPERATION**

1. GENERAL LIGHTING (A) AUTO ON TO 50% WHEN OCCUPANCY DETECTED.
2. MANUAL ON/OFF/DIM AND LIGHT REDUCTION CONTROL OF GENERAL LIGHTING (A, B) WITH DIMMER SWITCHES.
3. MANUAL ON/OFF/DIM WHITE BOARD LIGHTING (B) WITH DIMMER SWITCH.
4. AUTO OFF ALL LIGHTING WITHIN 20 MINUTES OF OCCUPANTS LEAVING.


**TYPICAL DRAWING DETAIL NOTES**

1. FOLLOW MANUFACTURER INSTRUCTIONS FOR PROPER PRODUCT PLACEMENT, INSTALLATION, WIRING AND OPERATION.
2. DIAGRAM IS TYPICAL FOR SPACE TYPE. PROVIDE PROPER QUANTITY AND TYPE OF OCCUPANCY SENSORS, SWITCHES, ROOM CONTROLLERS, DAYLIGHTING SENSORS, ETC., PER CODE REQUIREMENT FOR EACH SPACE.
3. USE PRE-TERMINATED CATSE CABLES WITH SPLITTERS AND COUPLERS AS NEEDED USING A FREE TOPOLOGY WIRING ARRANGEMENT TO CONNECT LIGHTING CONTROL DEVICES.
4. USE LM-MSTP WIRE TO DAISSY CHANGE CONNECT NETWORK BRIDGE DEVICES IN EACH ROOM. TWIST TOGETHER AND TAPE BACK THE SHIELDED WIRE AND DO NOT CONNECT TO NETWORK TERMINALS.
5. CONTRACTOR SHALL PROGRAM THE ROOM CONTROLLER FOR SEQUENCE OF OPERATION LISTED ABOVE.

**CEILING MOUNTED MOTION DETECTOR DETAIL**  
NOT TO SCALE



**EXTERIOR LIGHTING CONTROL DIAGRAM**  
NOT TO SCALE



- KEYNOTES:**
- ① ROUTE CIRCUIT THROUGH LIGHTING CONTACTOR; SEE EXTERIOR LIGHTING CONTROL DIAGRAM
  - ② 2#10,1#10 GND, 3/4" C
  - ③ ROUTE CIRCUIT THROUGH ROOM CONTROLLER; SEE CLASSROOM LIGHTING CONTROL DIAGRAM
  - ④ 3#10,1#10 GND, 3/4" C
  - ⑤ ROUTE CIRCUIT THROUGH ROOM CONTROLLER; SEE CORRIDOR LIGHTING CONTROL DIAGRAM



**GENERAL NOTES:**

- THE GENERAL CONTRACTOR SHALL NOTIFY THE ARCHITECT IMMEDIATELY OF ANY CONFLICTS/ DISCREPANCIES BETWEEN DISCIPLINES BEFORE ORDERING EQUIPMENT/MATERIALS.
- INSTALL OCCUPANCY SENSORS AND ACCESSORIES PER MANUFACTURER'S RECOMMENDATIONS.

**YATES ENGINEERING SOLUTIONS**

7159 Blue Jack Dr.  
Noyah, FL 32566  
Phone: (850)512-9579  
Email: quinn@yateseng.com  
FL PE No. 68326

**CONSTRUCTION DOCUMENTS**

**LIGHTING PLAN**

**PROJECT # 2409**

**FLORIDA**

**NEW STREAM BUILDING FOR HOLY NATIVITY EPISCOPAL SCHOOL**  
205 HAMILTON AVENUE  
PANAMA CITY

**E1.3**

**VBA DESIGN, INC.**  
ARCHITECTS AND PLANNERS  
2424 JENKS AVENUE, SUITE B  
PANAMA CITY, FLORIDA 32405  
"DESIGNING A BETTER EXPERIENCE"

**RAYMOND Q. YATES**  
REGISTERED PROFESSIONAL ENGINEER  
NO. 00826  
1-9-2025

**LICENSE NO. AP94000**  
PHONE: 850 769 3357  
FAX: 850 763 0410  
Reproduction or electronic transmission of these drawings or any part thereof is prohibited without written approval of the architect, VBA Design, Inc. These drawings are the property of VBA Design, Inc. and are not to be used for any other project without the written approval of VBA Design, Inc.